## Flange, closed, HxWxD=116x250x23mm

Powering Business Worldwide\*

Part no. FL3-X 093171 EL Number 4132064

(Norway)

| (Norway)                               |          |   |
|--|----------|---|
| General specifications                 |          |   |
| Product name                           | Ea       | aton xEnergy Safety Ci flange plate   |
| Part no.                               | FL       | .3-X  |
| EAN                                    | 40       | 015080931713  |
| Product Length/Depth                   | 11       | 15 millimetre   |
| Product height                         | 23       | 3 millimetre  |
| Product width                          | 20       | 05 millimetre   |
| Product weight                         | 0.1      | 192 kilogram  |
| Compliances                            | Ro       | oHS conform   |
| Product Tradename                      | xE       | Energy Safety Ci  |
| Product Type                           | Ad       | ccessories  |
| Product Sub Type                       | Fla      | ange plate  |
| Delivery program                       |          |   |
| Туре                                   | Ad       | ccessory for basic enclosures Basic enclosure xEnergy Safety Ci                                     |
| Model                                  | BI       | lind  |
| Accessory/spare part type              | Fla      | anges   |
| Technical Data - Mechanical            |          |   |
| Shape                                  | St       | traight   |
| Unit type                              | M        | lodular system  |
| Surface protection                     | Ur       | ntreated  |
| Material                               | PI       | lastic  |
| Degree of protection                   | Ot       | ther  |
| Number of connector holes              | 0        |   |
| Cable entry type                       | Dr       | rill as required  |
| Thickness                              | 4 1      | mm  |
| Thread type                            | No       | one   |
| Suitable for cable diameter - min      | 10       | mm  |
| Suitable for cable diameter - max      | 0 1      | mm  |
| Suitable for nominal thread (PG) - min | 16       |   |
| Suitable for nominal thread (PG) - max | 50       |   |
| Additional information                 |          |   |
| Special features                       |          | uick mounting using wedge-lock fasteners (included as standard) Sponge-rubber, aptive gasket        |
| Used with                              | Ac<br>xE | 50 mm (enclosure dimensions)<br>ccessory for basic enclosures<br>Energy Safety Ci<br>asic enclosure |

## **Technical data ETIM 9.0**

Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ecl@ss13-27-14-24-21 [ADI315012])

| Model              |    | Blind     |
|--------------------|----|-----------|
| Туре               |    | Straight  |
| Width              | mm | 205       |
| Height             | mm | 23        |
| Thickness          | mm | 4         |
| Material           |    | Plastic   |
| Surface protection |    | Untreated |

| Degree of protection (NEMA)              |    | Other   |
|--|----|---------|
| Pre-stamping                             |    | No      |
| Number of connector holes                |    | 0       |
| Suitable for cable diameter              | mm | 0 - 0   |
| Thread type                              |    | None    |
| Suitable for nominal thread metric/PG    |    | 16 - 50 |
| Gland plate type according to SEN 280901 |    |         |