

Door coupling rotary handle, black, lockable on the handle+switch, size 4



Part no. **NZM4-XTVDV-NA**
100686

General specifications		
Product name		Eaton Moeller series NZM operating element NA
Part no.		NZM4-XTVDV-NA
EAN		4015081005864
Product Length/Depth		230 millimetre
Product height		130 millimetre
Product width		230 millimetre
Product weight		1.78 kilogram
Compliances		UL/CSA IEC RoHS conform
Certifications		IEC60947 CSA certified UL (File No. E140305) CSA (Class No. 1437-01) CSA-C22.2 No. 5-09 UL489 CE marking UL listed CSA (File No. 22086) UL (Category Control Number DIHS)
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Operating element NA
Delivery program		
Type		Accessory Door coupling rotary handle
Features		Standard: black / gray Lockable
Special features		Complete including rotary drive and coupling parts Extension shaft additionally required. Cannot be combined with mechanical interlock External warning plate/ designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door
Frame		NZM4
Fitted with:		Padlock Extension shaft
Suitable for		Switch disconnecter Power circuit breaker
Used with		NZM4, N(S)4
Technical Data - Mechanical		
Color		Black
Cover/door type		Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door opens only with active rotation beyond the 0 position Door interlock not defeated in the locked OFF position.
Degree of protection / NEMA enclosure type		IP66 4X, 12
Lock number		Double lockable
Locking facility		With door interlock Lockable on the handle on the switch using up to 3 padlocks
Special features		Complete including rotary drive and coupling parts Extension shaft additionally required. Cannot be combined with mechanical interlock External warning plate/ designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])			
With restart blockage			No
With key lock			No
Padlock locking			Yes
Colour			Black
Suitable for emergency stop			No
With extension shaft			Yes
Suitable for power circuit breaker			Yes
Suitable for switch disconnecter			Yes
Degree of protection (NEMA)			4X, 12