

Miniature circuit breaker (MCB), 0.5 A, 3p, characteristic: C



Part no. **FAZ-C0,5/3-NA**
102237
EL Number **1691606**
(Norway)

General specifications		
Product name		Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB
Part no.		FAZ-C0,5/3-NA
EAN		4015081021130
Product Length/Depth		105 millimetre
Product height		75.5 millimetre
Product width		53.1 millimetre
Product weight		0.363 kilogram
Compliances		RoHS conform
Certifications		North America (UL listed, CSA certified) CE marking UL (File No. E235139) Specially designed for North America, suitable as BCPD CSA (File No. 204453) UL 489, CSA C22.2 No. 5 UL 489 IEC/EN 60947-2 CSA (Class No. 1432-01) UL (Category Control Number DIVQ) IEC 60947-2 CSA-C22.2 No. 5-09 EN45545-2 IEC 61373
Product Tradename		xEffect - FAZ-NA, FAZ-RT
Product Type		MCB
Product Sub Type		None
Delivery program		
Application		Feeder circuits, branch circuits Switchgear for export to North America (UL-listed)
Number of poles		Three-pole
Number of poles (total)		3
Number of poles (protected)		3
Tripping characteristic		C
Release characteristic		C
Amperage Rating		0.5 A
Type		FAZ-NA Miniature circuit breaker
Technical Data - Electrical		
Voltage type		AC
Voltage rating		277 V AC / 480 V AC
Voltage rating at DC		60 V DC
Voltage rating (IEC/EN 60947-2)		440 V
Voltage rating (UL)		480Y/277 V
Rated operational voltage (Ue) - max		415 V
Rated insulation voltage (Ui)		440 V
Rated impulse withstand voltage (Uimp)		4 kV
Frequency rating - min		50 Hz
Frequency rating - max		60 Hz
Rated switching capacity (IEC/EN 60947-2)		15 kA
Breaking capacity		10 kA (UL489)
Rated short-circuit breaking capacity (EN 60898) at 230 V		0 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V		0 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V		15 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V		15 kA

Selectivity class			3
Lifespan, electrical			20000 operations
Overvoltage category			III
Pollution degree			2
Direction of incoming supply			As required
Technical Data - Mechanical			
Frame			45 mm
Enclosure width			105 mm
Width in number of modular spacings			3
Built-in depth			70.5 mm
Mounting width			17.7 mm
Mounting width per pole			17.7 mm
Mounting Method			Top-hat rail IEC/EN 60715
Mounting position			As required
Degree of protection			IP40 (when fitted) IP20 UL/CSA Type: - IP20 (IEC)
Terminals (top and bottom)			Twin-purpose terminals
Connectable conductor cross section (solid-core) - min			1 mm ²
Connectable conductor cross section (solid-core) - max			25 mm ²
Connectable conductor cross section (multi-wired) - min			1 mm ²
Connectable conductor cross section (multi-wired) - max			25 mm ²
Terminal protection			Finger and hand touch safe, DGUV VS3, EN 50274
Tightening torque			UL: 2.4 Nm (21 lb-in) for AWG 18 - AWG 12 Max. 2.4 Nm UL: 2.8 Nm (25 lb-in) for AWG 10 - AWG 8 UL: 4 Nm (36 lb-in) for AWG 6
Design verification as per IEC/EN 61439 - technical data			
Rated operational current for specified heat dissipation (I _n)			0.5 A
Heat dissipation per pole, current-dependent			0 W
Equipment heat dissipation, current-dependent			3.5 W
Static heat dissipation, non-current-dependent			0 W
Heat dissipation capacity			0 W
Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			75 °C
Additional information			
Current limiting class			3
Features			Additional equipment possible
Functions			Current limiting circuit breaker
Special features			Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)			
Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss13-27-14-19-01 [AAB905019])			
Built-in depth		mm	70.5
Release characteristic			C
Number of poles (total)			3
Number of protected poles			3
Rated current		A	0.5
Rated voltage		V	415
Rated insulation voltage U _i		V	440
Rated impulse withstand voltage U _{imp}		kV	4
Rated short-circuit breaking capacity I _{cn} according to EN 60898 at 230 V		kA	0
Voltage type			AC
Rated short-circuit breaking capacity I _{cn} according to EN 60898 at 400 V		kA	0

Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V	kA	15
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	kA	15
Frequency	Hz	50 - 60
Power loss	W	
Current limiting class		3
Flush-mounted installation		No
Concurrently switching neutral conductor		No
Over voltage category		3
Pollution degree		2
Additional equipment possible		Yes
Width in number of modular spacings		3
Degree of protection (IP)		IP20
Ambient temperature during operating	°C	-25 - 75
Connectable conductor cross section multi-wired	mm ²	1 - 25
Connectable conductor cross section solid-core	mm ²	1 - 25
Explosion-proof		No