

Terminal plate, 3p, copper band up to 32x20 mm, 800A



Part no. BBA-TP3/CU-BAND
107186
EL Number 2465024
(Norway)

General specifications		
Product name		Eaton xEffect SASY 60i terminal plate
Part no.		BBA-TP3/CU-BAND
EAN		4015081069491
Product Length/Depth		130 millimetre
Product height		205 millimetre
Product width		255 millimetre
Product weight		1.79 kilogram
Compliances		RoHS conform
Product Tradename		xEffect SASY 60i
Product Type		Busbar system component
Product Sub Type		Terminal plate
Delivery program		
Type		60 mm system Connection
Technical Data - Electrical		
Rated operation current (Ie)		800 A
Rated operational current		800 A
Rated operational current (Ie) - max		800 A
Creepage resistance		CTI 200
Technical Data - Mechanical		
Material		Silicon free, chlorine free
Busbar thickness - min		5 mm
Busbar thickness - max		10 mm
Busbar width - min		20 mm
Busbar width - max		30 mm
Terminal contact area		32 mm x 25 mm
Terminal capacity (conductor)		32 mm x 1 mm (10x) 30 mm x 25 mm
Conductor cross section - max		750 mm ²
Width clamp		240 mm
Design verification as per IEC/EN 61439 - technical data		
Temperature resistance		Temperature resistant to 120 °C
Additional information		
Features		Self-extinguishing acc. UL 94
Functions		Connections Connection kit
Special features		Pole pitch adjustable Fixing direct over busbar terminals Including shroud with adjustable width Looping is possible
Suitable for		Flat rail Three-pole Strip conductor connection
Used with		25 mm x 5/10 mm rail Double T profile 30 mm x 5/10 mm rail 20 mm x 5/10 mm rail Connection 60 mm system

Technical data ETIM 9.0

Busbar thickness		mm	5 - 10
Busbar width		mm	20 - 30
Suitable for			Flat rail
Width clamp		mm	240
Max. conductor cross section		mm ²	750
Max. rated operation current I _e		A	800
Suitable for round conductor connection			No
Suitable for sector conductor connection			No
Suitable for strip conductor connection			Yes