



Bottom/Top coverstrip 75mm long, 35mm blind + 40mm foam gasket, IP20, for 600mm Sectionwidth, grey



Powering Business Worldwide™

Part no. XLST2J6C

Catalog No. 107680

EL-Nummer 2465265
(Norway)

Delivery program

Product range		Control centres XVTL
Basic function		Accessories
Product function		Accessories
Accessories		Bottom plates
Single unit/Complete unit		Accessories
Description		Bottom plates as blanking covers adjustable from 60 - 75 mm Cable bushings < # 50 mm possible when using 2 XSPBA... # 50 - 80 mm cable bushings possible when using an XSPBA... in conjunction with XVTL-BP/JL
Function		for downward separation and for cable entries
Material		Sheet steel 1.5 mm
Surface finish		RAL 7035, light grey
Information about equipment supplied		Including screws
Suitable for depth		60 - 75
Suitable for width		600
Cableway		< Ø 50 mm

Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Component for installation (switchgear cabinet) (EC002620)			
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Elements for switching cabinet, housing, rack / Component for installation (electrical cabinet) (ecl@ss10.0.1-27-18-28-11 [ACN627011])			
Model			Floor plate
Suitable for enclosure building width		mm	600
Suitable for enclosure building height		mm	0
Suitable for enclosure building depth		mm	0
Width		mm	500
Height		mm	20
Depth		mm	75
Max. load capacity		kg	0
Material			Metal
Colour			Grey
RAL-number			7035