

Auxiliary contact, for FAZ-NA, FAZ-RT, 1N/O+1N/C, 0.5HP

Part no. **Z-IHK-NA**
113895

General specifications	
Product name	Eaton Distribution parts
Part no.	Z-IHK-NA
EAN	4015081134052
Product Length/Depth	96 millimetre
Product height	75 millimetre
Product width	8.8 millimetre
Product weight	0.048 kilogram
Compliances	RoHS conform
Certifications	IEC/EN 60898 CSA-C22.2 No. 5-09 UL 489 North America (UL listed, CSA certified) CE marking UL (Category Control Number DIHS, DIHS7) CSA (Class No. 1437-01) CSA (File No. 204453) UL (File No. E257181) EN45545-2 IEC 61373
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes
Product Specification Details	
Accessory/spare part type	Auxiliary contacts
Additional equipment required	Auxiliary switch
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Amperage Rating	6 A
Application	Switchgear for export to North America (UL-listed)
Assembly width	0.5
Contact function	1 M + 1 B
Conventional thermal current Ith of auxiliary contacts (1-pole, open)	6 A
Degree of protection	IP20 (IEC) UL/CSA Type: - IP40
Device fitting	Miniature circuit breaker (MCB)
Enclosure width	80 mm
Frame	Standard front dimension: 45 mm
Frequency rating	50 Hz / 60 Hz
Functions	Auxiliary switch
Mounting width	8.8 mm (0.5 space units)
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	2
Number of switches (fault signal)	0
Rated conditional short-circuit current (Iq) with 6 a back-up fuse	1 kA
Rated impulse withstand voltage (Uimp)	4 kV
Rated insulation voltage (Ui)	250 V AC
Rated operational current	0.5 A (110 V DC-13)

			2 A (250 V AC-15) 3 A (250 V AC-12)
Rated operational voltage (Ue) - max			250 V
Rated switch current			6 A
Suitable for current of main contact unit - max			6 A
Terminal protection			Busbar tag shroud to BGV A3
Terminal type			Lift terminals
Type			Accessory Accessory for miniature circuit breaker
Used with			Auxiliary contacts Accessory for miniature circuit breaker Accessory
Voltage rating			250 V AC
Voltage rating per contact - min			5 V DC
Voltage type			AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])			
Device fitting			Miniature circuit breaker (MCB)
Function			Auxiliary switch
Width in number of modular spacings			0.5
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	6
Rated voltage		V	250
Voltage type			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			2
Suitable for max. current main contact unit		A	6