

Busbar support, outside, universal, KSX



Part no. **KSX-34P-EXT**
138268

| General specifications | | |
|--------------------------------------|--|--|
| Product name | | Eaton xEnergy Light LV systems LV switchgear |
| Part no. | | KSX-34P-EXT |
| EAN | | 4015081350483 |
| Product Length/Depth | | 300 millimetre |
| Product height | | 300 millimetre |
| Product width | | 30 millimetre |
| Product weight | | 4.58 kilogram |
| Compliances | | RoHS conform |
| Product Tradename | | xEnergy Light |
| Product Type | | LV systems |
| Product Sub Type | | LV switchgear |
| Product Specification Details | | |
| Busbar distance | | 0 mm |
| Current rating - max | | 3200 A |
| Functions | | Busbar support KSX busbar support external, universal |
| Impulse withstand current | | 110 kA |
| Number of poles | | Four-pole |
| Rated operation current (Ie) | | 3200 A |
| Special features | | For outdoor use in xEnergy type-tested power distribution systems and XVTL distribution panel Including fixing bracket, fixing screws and supports for covers |
| Suitable for | | Four-pole Three-pole |
| Type | | Distribution board feeder system KSX-System |
| Used with | | 30 x 10 mm Double T profile Triple T profile KSX-System Distribution board feeder system |

Technical data ETIM 9.0

| | | | |
|--|--|----|------|
| Energy distribution systems (EG000015) / Busbar support (EC001166) | | | |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar carrier (ecl@ss13-27-40-06-07 [AC0377016]) | | | |
| Number of poles | | | 4 |
| Max. rated current | | A | 3200 |
| Busbar distance | | mm | 0 |