

Conductor connection terminal M10 for 10mm



Part no. **AKU-M10/10**
138361

General specifications		
Product name		Eaton xEffect SASY 60i busbar terminal
Part no.		AKU-M10/10
EAN		4015081351411
Product Length/Depth		47 millimetre
Product height		42 millimetre
Product width		38 millimetre
Product weight		0.362 kilogram
Compliances		RoHS conform
Product Tradename		xEffect SASY 60i
Product Type		Busbar system component
Product Sub Type		Busbar terminal
Delivery program		
Type		185 mm system 60 mm system Compact system Connection
Technical Data - Electrical		
Rated operation current (Ie)		630 A
Rated operational current		630 A
Rated operational current (Ie) - max		630 A
Technical Data - Mechanical		
Busbar thickness - min		10 mm
Busbar thickness - max		10 mm
Busbar width - min		0 mm
Busbar width - max		0 mm
Terminal contact area		10 mm with M10 bolt
Terminal capacity (conductor)		Cable lugs M10
Conductor cross section - max		0 mm ²
Width clamp		38 mm
Additional information		
Functions		Universal conductor connection terminal Connections
Special features		With integrated retaining spring, open terminal chamber and captive terminal screw
Suitable for		Round conductor connection Flat rail
Used with		All 10 mm thick flat busbars Double T profile

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Terminal block systems and system components / Terminal block systems / Busbar terminal (ecl@ss13-27-25-01-16 [BAA025018])			
Busbar thickness	mm	10 - 10	
Busbar width	mm	0 - 0	
Suitable for		Flat rail	
Width clamp	mm	38	
Max. conductor cross section	mm ²	0	
Max. rated operation current Ie	A	630	
Suitable for round conductor connection		Yes	
Suitable for sector conductor connection		No	

