

Connection terminal 95-300 mm²

Part no. **AK300**
138363



General specifications		
Product name		Eaton xEffect SASY 60i busbar terminal
Part no.		AK300
EAN		4015081351435
Product Length/Depth		100 millimetre
Product height		60 millimetre
Product width		48 millimetre
Product weight		0.857 kilogram
Compliances		RoHS conform
Product Tradename		xEffect SASY 60i
Product Type		Busbar system component
Product Sub Type		Busbar terminal
Delivery program		
Type		60 mm system Connection
Technical Data - Electrical		
Rated operation current (Ie)		630 A
Rated operational current		630 A
Rated operational current (Ie) - max		630 A
Technical Data - Mechanical		
Busbar thickness - min		10 mm
Busbar thickness - max		10 mm
Busbar width - min		30 mm
Busbar width - max		30 mm
Terminal capacity (conductor)		95 mm ² - 300 mm ²
Conductor cross section - max		300 mm ²
Width clamp		48 mm
Additional information		
Functions		Connections Terminal
Special features		Cable block is used to connect the conductor to the busbar
Suitable for		Strip conductor connection Round conductor connection T-rail
Used with		Triple T profile 30 mm x 10 mm rail Double T profile Connection 60 mm system

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Terminal block systems and system components / Terminal block systems / Busbar terminal (ecl@ss13-27-25-01-16 [BAA025018])			
Busbar thickness		mm	10 - 10
Busbar width		mm	30 - 30
Suitable for			T-rail
Width clamp		mm	48
Max. conductor cross section		mm ²	300
Max. rated operation current Ie		A	630
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			No

