

Base module washer XI/ON, tension spring, 4 connection levels



Part no. XN-S4T-SBBS
140081
EL Number 4520616
(Norway)

| General specifications | | |
|-------------------------------------|--|--|
| Product name | | Eaton XN Rack |
| Part no. | | XN-S4T-SBBS |
| EAN | | 7640130121225 |
| Product Length/Depth | | 128.9 millimetre |
| Product height | | 49.9 millimetre |
| Product width | | 12.6 millimetre |
| Product weight | | 0.038 kilogram |
| Certifications | | CSA Class No.: 2252-01, 2252-81 Certified by UL for use in Canada IEC/EN 61000-6-2 UL Category Control No.: NRAQ, NRAQ7 Rated data for terminations according to IEC/EN 60947-7-1 UL File No.: E205091 UL report applies to both US and Canada IEC/EN 6113-2 CSA-C22.2 No. 142 CE, cUL IEC/EN 61000-6-4 IEC/EN 61131-2 UL Recognized UL 508 CE |
| Product Tradename | | XN |
| Product Type | | Rack |
| Product Sub Type | | None |
| Features & Functions | | |
| Fitted with: | | Pluggable modules, analog I/O Pluggable modules, others Power supply Pluggable modules, central modules Pluggable modules, digital I/O Pluggable modules, communication modules Pluggable modules, function and technology modules |
| General information | | |
| Degree of protection | | IP20 |
| Mounting method | | Rail mounting possible |
| Number of connection levels | | 4 |
| Type | | XI/ON slice card base module |
| Used with | | XN-2AI-U (-10 - 10 V DC) XN-2DO-R-CO XN-1RS485/422 XN-2DO-R-NC XN-2DO-R-NO XN-2AI-PT/NI-2/3 XN-1AI-I(0 - 20 mA) XN-1SSI XN-2AI-I(0 - 20 mA) XN-1AI-U (-10 - 10 V DC) XN-4DI-24VDC-P XN-1CNT-24VDC XN-1RS232 XN-4DI-24VDC-N |
| Voltage type | | DC |
| Ambient conditions, mechanical | | |
| Drop and topple | | According to IEC 60068-2-31, free fall according to IEC 60068-2-32 |
| Shock resistance | | Continuous according to IEC/EN 60068-2-29 Mechanical, According to IEC/EN 60068-2-27 |
| Vibration resistance | | According to IEC/EN 60068-2-6 |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | 0 °C |

| | | |
|--|--|--|
| Ambient operating temperature - max | | 55 °C |
| Environmental conditions | | Harmful gasses - SO2: 10 ppm (relative humidity < 75%, no condensation) Harmful gasses - H2S: 1 ppm (relative humidity < 75%, no condensation) |
| Relative humidity | | 5 - 95 % (indoor, Level RH-2, non-condensing for storage at 45°C) |
| Electro magnetic compatibility | | |
| Air discharge | | Air/contact discharge according to IEC/EN 61000-4-2 |
| Burst impulse | | According to IEC/EN 61000-4-4 |
| Electromagnetic fields | | According to IEC EN 61100-4-2 |
| Emitted interference | | 230 - 1000 MHz (radiated, high frequency, according to EN 55016-2-3) 30 - 230 MHz (radiated, high frequency, according to EN 55016-2-3) |
| Radiated RFI | | IEC/EN 61100-4-6 |
| Surge rating | | According to IEC/EN 61000-4-5 Level 4 |
| Voltage dips | | According to EN 61131-2 (Voltage fluctuations/voltage dips) |
| Terminal capacities | | |
| Terminal capacity | | 0.5 - 2.5 mm ² , solid, H07V-U 0.5 - 1.5 mm ² , with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.5 - 1.5 mm ² , flexible without ferrule, H07V-K 0.5 - 1.5 mm ² , with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) |
| Gauge pin | | A1 (according to IEC/EN 60947-1) |
| Stripping length (main cable) | | 8 mm |
| Communication | | |
| Connection type | | Spring-loaded/screw terminal, Connection design in TOP direction |
| Number of slots | | 1 |
| Input/Output | | |
| Input current at AC - max | | 0 A |
| Input voltage at AC 50 Hz - min | | 0 V |
| Input voltage at AC 50 Hz - max | | 0 V |
| Input voltage at DC - min | | 0 V |
| Input voltage at DC - max | | 0 V |
| Output current at AC, 50 Hz - max | | 0 A |
| Output voltage at AC 50 Hz - max | | 0 V |
| Output voltage at DC - min | | 0 V |
| Output voltage at DC - max | | 0 V |
| Safety | | |
| Explosion safety category for dust | | None |
| Explosion safety category for gas | | None |
| Potential isolation | | Through optocoupler: yes |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0 W |
| Rated operational current for specified heat dissipation (I _n) | | 0 A |
| Static heat dissipation, non-current-dependent P _{vs} | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Meets the product standard's requirements. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |

| | | |
|--|--|--|
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Fieldbus, decentr. periphery - mounting frame (EC001598)

Electric engineering, automation, process control engineering / Control, Process Control System (PCS) / Field bus, decentralized peripheral / Field bus, decentralized peripheral - module carrier (ecl@ss13-27-24-26-03 [BAA064018])

| | | |
|---|----|-------|
| With integrated power supply | | Yes |
| Input voltage AC 50 Hz | V | 0 - 0 |
| Input voltage AC 60 Hz | V | 0 - 0 |
| Input voltage DC | V | 0 - 0 |
| Type of voltage (input voltage) | | DC |
| Max. input current AC 50 Hz | A | 0 |
| Max. input current AC 60 Hz | A | 0 |
| Max. input current DC | A | 0 |
| Output voltage AC 50 Hz | V | 0 - 0 |
| Output voltage AC 60 Hz | V | 0 - 0 |
| Output voltage DC | V | 0 - 0 |
| Type of output voltage | | DC |
| Max. output current AC 50 Hz | A | 0 |
| Max. output current AC 60 Hz | A | 0 |
| Max. output current DC | A | 0 |
| System accessory | | Yes |
| Number of slots | | 1 |
| With pluggable modules, digital I/O | | Yes |
| With pluggable modules, analogue I/O | | Yes |
| With pluggable modules, communication modules | | Yes |
| With pluggable modules, function and technology modules | | Yes |
| With pluggable modules, central modules | | Yes |
| With pluggable modules, others | | Yes |
| Rail mounting possible | | Yes |
| Wall mounting/direct mounting | | No |
| Front built-in possible | | No |
| Rack-assembly possible | | No |
| Suitable for safety functions | | No |
| SIL according to IEC 61508 | | None |
| Performance level according to EN ISO 13849-1 | | None |
| Appendant operation agent (Ex ia) | | No |
| Appendant operation agent (Ex ib) | | No |
| Explosion safety category for gas | | None |
| Explosion safety category for dust | | None |
| Width | mm | 12.6 |
| Height | mm | 49.9 |
| Depth | mm | 128.9 |