



Proximity Sensor, M30, analog, $S_n=1-12\text{mm}$, 15-30VDC, 0-20mA, 0-10V, line 2m

Part no. E59-A30A112C02-CV
 Catalog No. 166719
 Alternate Catalog No. E59-A30A112C02-CV

Delivery program

Basic function			Inductive Sensors
Product range			E59 AccuProx Series
Description			Current output (0 - 20 mA) and voltage output (0 - 10 V)
Connection			3-wire/4-wire
Design (outer dimensions)		mm	M30 x 1.5
Rated operational voltage	U_e		15 - 30 V DC
Rated switching distance	S_n	mm	1 - 12
Type of mounting			Flush
Switching type			Analog
For connection of:			2 m connection cable
Material			Stainless steel
Degree of Protection			IP67

Technical data

General

Standards			IEC/EN 60947-5-2
Ambient temperature			-40 - +70
Mechanical shock resistance		g	30 Shock duration 11 ms
Degree of Protection			IP67

Characteristics

Repetition accuracy of S_n		%	1
Temperature drift of S_n		%	10
Rated operational voltage	U_e		15 - 30 V DC
Switching state display		LED	Red
Operating voltage display		LED	Green
Connection			3-wire/4-wire
Style			
Design (outer dimensions)		mm	M30 x 1.5
For connection of:			2 m connection cable
Material			Stainless steel

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Sensors (EG000026) / Inductive proximity switch (EC002714)			
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Proximity switch / Inductive proximity switch (ecl@ss10.0.1-27-01-01 [AGZ376015])			
Width sensor		mm	0
Height of sensor		mm	0
Length of sensor		mm	69.6
Diameter sensor		mm	30
Mechanical mounting condition for sensor			Concise

Switching distance	mm	12
Suitable for safety functions		No
Type of switch function		Other
Type of switching output		Other
Type of electric connection		Cable
Number of semiconductor outputs with signalling function		0
Number of contact energized outputs with signalling function		0
Number of protected semiconductor outputs		0
Number of protected contact energized outputs		0
Type of actuation		Metallic Target
Type of interface		None
Type of interface for safety communication		None
Construction type housing		Cylinder, screw-thread
Coating housing		Other
Cascadable		No
Category according to EN 954-1		B
SIL according to IEC 61508		None
Performance level acc. EN ISO 13849-1		None
Max. output current at protected output	mA	20
Supply voltage	V	15 - 30
Rated control supply voltage Us at AC 50HZ	V	0 - 0
Rated control supply voltage Us at AC 60HZ	V	0 - 0
Rated control supply voltage Us at DC	V	15 - 30
Voltage type		DC
Switching frequency	Hz	140
With monitoring function downstream switching devices		No
Material housing		Metal
Compression-resistant		No
Explosion safety category for gas		None
Explosion safety category for dust		None
Interference resistance to magnetic fields		

Approvals

Product Standards		UL 508; CSA-C22.2 No. 14; IEC60947-5-2; CE marking
UL File No.		E166051
UL Category Control No.		NRKH, NRKH7
CSA File No.		50513
CSA Class No.		3211-03
North America Certification		UL listed, CSA certified
Max. Voltage Rating		30 V DC
Degree of Protection		IEC: IP67; UL/CSA Type: 4, 4x, 6, 6P, 12, 13

Assets (links)

Declaration of CE Conformity

00003158

Instruction Leaflets

IL05301010Z2018_05

Additional product information (links)

IL05301010Z AccuProx Series Analog Inductive Sensors

IL05301010Z AccuProx Series Analog Inductive Sensors ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL05301010Z2018_05.pdf