

Main choke, three-phase, 550 V + 0% (50/60 Hz), V AC, 303 A, 0.06 mH

 Part no. **DX-LN3-303**  
**169143**

<b>General specifications</b>	
Product name	Eaton DX Mains choke
Part no.	DX-LN3-303
EAN	4015081656219
Product Length/Depth	400 millimetre
Product height	500 millimetre
Product width	600 millimetre
Product weight	18.6 kilogram
Certifications	IEC/EN 61558-2-20-2000 CSA CSA-C22.2 No. 14 UL File No.: E167225 IEC/EN61800-5 UL report applies to both US and Canada UL Category Control No.: XPTQ2, XPTQ8 CE UL UL 508C VDE 0570 Part 2-20/2001-04 Certified by UL for use in Canada IEC/EN61800-3
Product Tradename	DX
Product Type	Accessory
Product Sub Type	Mains choke
<b>Features &amp; Functions</b>	
Fitted with:	Connection lugs PE stud
Number of phases	3
Number of poles	Three-pole
<b>General information</b>	
Bore diameter	14 mm
Degree of protection	IP00 NEMA Other
Duty factor	100 %
Insulation class	B
Product Category	Accessories
Suitable as	Net reactance coil
Suitable for	Branch circuits, (UL/CSA)
Switching frequency	3 kHz
Used with	DA1, DG1, SPX, SVX
<b>Ambient conditions, mechanical</b>	
Mounting position	Free surrounding areas > 50 mm Standing vertically Suspended horizontally
Shock resistance	3 shocks Shock duration: 11 ms
Vibration resistance	0 - 150 Hz, 1 g 10 - 55 Hz, 0.35 mm
<b>Climatic environmental conditions</b>	
Altitude	Max. 5000 m with current reduction Max. 1000 m
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-25 °C
Ambient storage temperature - max	85 °C
Ambient storage temperature - min	-25 °C
Operating temperature details	-25 - 40 °C (up to 70 °C with current derating)

<b>Terminal capacities</b>		
Tightening torque		15.5 Nm, Screw terminals
<b>Connection</b>		
Connection lug		Cu 40 x 5 mm <sup>2</sup>
<b>Electrical rating</b>		
Permissible connection voltage		Max. 550 V AC (50/60 Hz)
Rated current (Ith) at rated voltage DC - max		0 A
Rated frequency - min		50 Hz
Rated frequency - max		60 Hz
Rated inductance		0.06 mH
Rated operational current (Ie) - min		303 A
Rated operational current (Ie) - max		303 A
Rated operational voltage (Ue) - max		550 V
Relative short-circuit voltage		0 %
Voltage rating - max		480 V
Voltage sag Uk		2.5 %
<b>Design verification</b>		
Heat dissipation capacity Pdiss		0 W
Rated operational current for specified heat dissipation (In)		303 A
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Coil for low-voltage (EC002563)		
Electric engineering, automation, process control engineering / Electronic coil and filter / Electronic choke coil / Electronic choke coil (unspecified) (ecl@ss13-27-42-01-90 [ADJ199012])		
Suitable as interference suppression reactance coil		No
Suitable as net reactance coil		Yes
Suitable as commutation reactance coil		No
Suitable as ripple filter choke		No
Suitable as output reactance coil		No
Number of poles, primary side		3
Rated clock frequency	kHz	3
Rated operating frequency	Hz	50 - 60

Max. rated operation voltage Ue	V	550
Rated current AC	A	303 - 303
Max. rated current (Ith) at rated voltage DC	A	0
Rated inductance	mH	0.06
Degree of protection (IP)		IP00
Relative short circuit voltage	%	0
Resonance frequency	Hz	0
Degree of protection (NEMA)		Other