



**Fuse-link, high speed, 4000 A, AC 1000 V, 300 kA, 2 x size 4, 105 x 250 x 87 mm, aR, IEC, type K indicator**



**Part no. FUSE 4000A 1000V 24BKE/85 AR**  
**Catalog No. 170M7530**

**Delivery program**

|                              |   |    |                                     |
|------------------------------|---|----|-------------------------------------|
| Product range                |   |    | Fuse                                |
| Basic function               |   |    | Fuse-link                           |
| Field of application         |   |    | high speed                          |
| Rated current                | I | A  | 4000                                |
| Rated voltage                |   |    | AC 1000 V                           |
| Construction size            |   |    | 2 x size 4                          |
| Size                         |   |    | 105 x 250 x 87 mm                   |
| Utilization category         |   |    | aR                                  |
| Status indicator             |   |    | type K indicator                    |
| Breaking Capacity            |   | kA | 300                                 |
| usable for size/applications |   |    | Protection of power rectifiers      |
| Standard/Approval            |   |    | IEC                                 |
| Shape                        |   |    | square body with flush end contacts |
| Standards/Regulations        |   |    | IEC 60269-4                         |

**Technical data ETIM 7.0**

|   |  |    |   |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |   |
| Construction size   |  |    | Other                                     |
| Rated current   |  | A  | 4000                                      |
| Rated voltage   |  | V  | 1000                                      |
| Voltage type  |  |    | AC  |
| Rated switching capacity  |  | kA |   |
| Utilization category  |  |    | aR (accompanied semiconductor protection) |
| Type of fuse status indicator   |  |    | Other                                     |
| Insulated metal gripping lugs (IMGL)  |  |    | No  |