

## Overload relay function, 24 V DC

**Part no.** PKE-XZMR(24VDC)  
**173425**  
**EL Number** 4315148  
**(Norway)**

<b>General specifications</b>	
Product name	Eaton Moeller® series PKE Overload relay module
Part no.	PKE-XZMR(24VDC)
EAN	4015081698288
Product Length/Depth	105 millimetre
Product height	50 millimetre
Product width	105 millimetre
Product weight	0.079 kilogram
Compliances	CE
Product Tradename	PKE
Product Type	Accessory
Product Sub Type	Overload relay module
Catalog Notes	1 N/C: for switching off the contactor 1 N/O: for trip indication External control voltage supply required.
<b>Features &amp; Functions</b>	
Features	Status display via LED
Functions	Adjustable manual/auto reset Overload relay function (the motor-protective circuit-breaker will not trip in the event of an overload)
<b>General information</b>	
Class	Other
Lifespan, electrical	200,000 Operations
Lifespan, mechanical	5,000,000 Operations
Mounting method	Direct attachment
Overvoltage category	III
Pollution degree	3
Rated impulse withstand voltage (Uimp)	6000 V AC
Voltage type	DC
<b>Ambient conditions, mechanical</b>	
Mounting position	Right side (of PKE motor-protective circuit-breakers with advanced PKE-XTU...A... trip blocks)
<b>Climatic environmental conditions</b>	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
<b>Terminal capacities</b>	
Terminal capacity (solid/flexible with ferrule)	0.75 - 2.5 mm <sup>2</sup>
Terminal capacity (solid/stranded AWG)	18 - 14
<b>Electrical rating</b>	
Operational voltage	0.8 - 1.1 x Us
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V	7777777 A
Rated operational current (Ie) at DC-13, 24 V	1.5 A
Rated operational voltage (Ue) at AC - max	7777777 V
Rated operational voltage (Ue) at DC - max	250 V
Safe isolation	440 V, Between auxiliary contacts and main contacts, According to EN 61140
<b>Short-circuit rating</b>	
Short-circuit protection rating	6 A gG/gL, Fuse, Contacts
<b>Magnet system</b>	
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V

Rated control supply voltage (Us) at AC, 50 Hz - max		0 V
Rated control supply voltage (Us) at AC, 60 Hz - min		0 V
Rated control supply voltage (Us) at AC, 60 Hz - max		0 V
Rated control supply voltage (Us) at DC - min		24 V
Rated control supply voltage (Us) at DC - max		24 V
<b>Contacts</b>		
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		1
Number of auxiliary contacts (normally open contacts)		1
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
<b>Power consumption</b>		
Power consumption (pick-up) at DC		0.5 W
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0.017 W
Rated operational current for specified heat dissipation (In)		1.5 A
Static heat dissipation, non-current-dependent Pvs		0.61 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Electronic overload relay (EC001080)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Electronic overload relay (ecl@ss13-27-37-15-02 [AKF076019])		
Mounting method		Direct attachment
Type of electrical connection of main circuit		Other
Adjustable current range	A	0 - 0
External power supply required		No
Rated control supply voltage AC 50 Hz	V	0 - 0
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	24 - 24
Voltage type for actuating		DC

Number of auxiliary contacts as normally closed contact			1
Number of auxiliary contacts as normally open contact			1
Number of auxiliary contacts as change-over contact			0
Voltage type (operating voltage)			
Operating voltage AC 50 Hz		V	
Operating voltage AC 60 Hz		V	
Operating voltage DC		V	
Rated switch current		A	
Release class			Other
Reset function automatic			Yes
Reset function input			No
Reset function push-button			Yes
Width		mm	105
Height		mm	50
Depth		mm	105