

POP protection device, 1 pole, 230 V AC, 50 Hz



Part no. **A-POP**
173574

| General specifications | | |
|---|--|---|
| Product name | | Eaton Distribution parts |
| Part no. | | A-POP |
| EAN | | 4015081699810 |
| Product Length/Depth | | 85.5 millimetre |
| Product height | | 76 millimetre |
| Product width | | 25 millimetre |
| Product weight | | 0.088 kilogram |
| Compliances | | RoHS conform |
| Product Tradename | | None |
| Product Type | | Distribution parts |
| Product Sub Type | | None |
| Public Consumption | | Yes |
| Product Family Description | | ES-PMCC-PDC-Eaton Distribution parts |
| Globally Marketable | | Yes |
| Product Specification Details | | |
| Additional equipment required | | Monitoring unit |
| Assembly width | | 1 |
| Device fitting | | Earth leakage circuit breaker and miniature circuit breaker (MCB) |
| Functions | | Other function |
| Number of contacts (change-over contacts) | | 0 |
| Number of contacts (normally closed contacts) | | 0 |
| Number of contacts (normally open contacts) | | 1 |
| Number of poles at main contact unit - max | | 4 |
| Number of switches (fault signal) | | 0 |
| Rated operational voltage (Ue) - max | | 230 V |
| Rated switch current | | 0 A |
| Suitable for current of main contact unit - max | | 63 A |
| Voltage type | | AC |

Technical data ETIM 9.0

| Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286) | | |
|---|---|---|
| Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018]) | | |
| Device fitting | | Earth leakage circuit breaker and miniature circuit breaker (MCB) |
| Function | | Other |
| Width in number of modular spacings | | 1 |
| Number of contacts as normally open contact | | 1 |
| Number of contacts as normally closed contact | | 0 |
| Number of contacts as change-over contact | | 0 |
| Number of fault-signal switches | | 0 |
| Rated switch current | A | 0 |
| Rated voltage | V | 230 |
| Voltage type | | AC |
| With auto test for earth leakage function | | No |
| Suitable for max. number of poles main contact unit (total) | | 4 |
| Suitable for max. current main contact unit | A | 63 |