



EWP wall-mount enclosure for EP standard mounting units, IP54, protection class 2, RAL9016, without EP modules, HxWxB=1400x1300x225mm

Part no. EWP-13142
Catalog No. 174696
Alternate Catalog No. EWP-13142
EL-Nummer 2455884
(Norway)

Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|---|----------------|---|--|
| Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 | | | |
| Individual enclosure for wall mounting | P _V | W | 207 |
| Starting enclosure for wall mounting | P _V | W | 209 |
| Middle enclosure for wall mounting | P _V | W | 202 |
| Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 | | | |
| Individual enclosure for wall mounting | P _V | W | 416 |
| Starting enclosure for wall mounting | P _V | W | 420 |
| Middle enclosure for wall mounting | P _V | W | 405 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | 750 °C; meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Not relevant to indoor installations. |
| 10.2.5 Lifting | | | Does not apply to enclosures without lifting aids. |
| 10.2.6 Mechanical impact | | | IK09 |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | IP54 |
| 10.4 Clearances and creepage distances | | | Is the panel builder's responsibility. |
| 10.5 Protection against electric shock | | | Protection class 2, therefore not applicable. |
| 10.6 Incorporation of switching devices and components | | | Is the panel builder's responsibility. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | U _i = 400 V AC |
| 10.9.3 Impulse withstand voltage | | | 3 kV |
| 10.9.4 Testing of enclosures made of insulating material | | | Does not apply to metal enclosures. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | | Meets the product standard's requirements. |

Technical data ETIM 7.0

| | | | |
|--|--|----|-------|
| Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261) | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss10.0.1-27-18-01-01 [AGZ056016]) | | | |
| Width | | mm | 1300 |
| Height | | mm | 1400 |
| Depth | | mm | 225 |
| Material | | | Steel |

| | | | |
|---------------------------------|--|--|----------------|
| Material quality | | | |
| Surface finishing | | | Powder coating |
| Colour | | | White |
| RAL-number | | | 9016 |
| With mounting plate | | | No |
| Mounting plate depth-adjustable | | | No |
| Number of locks | | | 1 |
| Floor installation possible | | | No |
| Wall fastening possible | | | Yes |
| Wall build in | | | Yes |
| Pole fastening | | | No |
| Tackable | | | Yes |
| Number of doors | | | 2 |
| Suitable for metrical mounting | | | Yes |
| Suitable for outdoor set-up | | | No |
| Pitched roof | | | No |
| EMC-version | | | No |
| With glazed door | | | No |
| With ventilation door | | | No |
| With backside door | | | No |
| Impact strength | | | IK09 |
| Degree of protection (IP) | | | IP54 |
| Degree of protection (NEMA) | | | |

Dimensions



