

Base module; 800-mm aluminum tube and foot



Part no. **SL7-CB-800**
177312

General specifications		
Product name		Eaton Moeller® series SL7 Base module
Part no.		SL7-CB-800
EAN		4015081717651
Product Length/Depth		73 millimetre
Product height		903 millimetre
Product width		73 millimetre
Product weight		0.8 kilogram
Certifications		IEC/EN 60947-5-1 IEC/EN 60529
Product Tradename		SL7
Product Type		Base module
Product Sub Type		None
Features & Functions		
Color		Other
Fitted with:		Cover Aluminum tube Plastic foot
Number of modules		Max. 5 Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
General information		
Connection to SmartWire-DT		No
Degree of protection		NEMA 13 NEMA 4X IP66 NEMA 4
Mounting Method		Floor Bracket Horizontal
Mounting position		As required
Overvoltage category		III
Pollution degree		3
Product Category		SL signal towers
Rated impulse withstand voltage (Uimp)		4000 V AC
Shock resistance		15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Tube length		800 mm
Type		Base module
Climatic environmental conditions		
Ambient operating temperature - min		-30 °C
Ambient operating temperature - max		60 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacities		
Terminal capacity (AWG)		24 - 14
Terminal capacity (flexible with ferrule and plastic collar)		0.25 - 1.5 mm ²
Terminal capacity (solid/flexible)		0.13 - 2.5 mm ²
Electrical rating		
Rated insulation voltage (Ui)		250 V
Rated operational voltage		230/240 V AC ± 10 % 24 V AC/DC ± 10 % 110/120 V AC ± 10 %

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module
(ec1@ss13-27-37-12-32 [AKF050019])

Connection type auxiliary circuit			Spring clamp connection
Suitable for tube mounting			No
Suitable for angle mounting			Yes
Suitable for floor mounting			Yes
Colour			Other
Suitable for AS interface			No
Suitable for M12 connector			No
Suitable for IO link			No