

Part no. IZMX16B4-P16W-1
183461
EL Number 4398075
(Norway)

General specifications	
Product name	Eaton Moeller series IZMX/INX circuit-breaker
Part no.	IZMX16B4-P16W-1
EAN	4015081791972
Product Length/Depth	584 millimetre
Product height	597 millimetre
Product width	521 millimetre
Product weight	32.49 kilogram
Compliances	IEC IEC/EN 60947 RoHS conform
Product Tradename	IZMX/INX
Product Type	Circuit-breaker
Product Sub Type	None
Delivery program	
Type	Air circuit breakers/switch-disconnector Open circuit breaker
Number of poles	Four-pole
Amperage Rating	1600 A
Release system	Electronic release
Features	Motor drive optional Complete device with protection unit
Special features	Cassette must be separately ordered. External IZMX-DTP-PTM-1 voltage measuring module required (1 module is suitable for 16 circuit breakers) IZMX-DTP-PTM external voltage measuring module required suitable for zone selectivity suitable for communication with integrated system monitor with integrated test possibility With graphic LCD display optionally fittable by user with comprehensive accessories Terminal capacity hint: These are values used in separate switchgear. The actual values will depend on the temperature around the circuit breaker, which is influenced by the ambient temperature, the degree of protection (IP), the mounting height, the partitions, and any external ventilation. Depending on the specific switchgear design, this may result in derating, which can then be compensated for by increasing the cross-sectional area. Temperature rise tests in the specific switchgear can provide specific and detailed information.
Frame	IZMX16
Fitted with:	Switched-off indicator
Used with	Air circuit breakers/switch-disconnector Open circuit breaker
Technical Data - Electrical	
Voltage rating at AC	690 V AC
Rated operating voltage (Ue) - min	690 V
Rated operating voltage (Ue) - max	690 V
Rated insulation voltage (Ui)	1000 V
Rated impulse withstand voltage (Uimp)	12 kV AC
Rated uninterrupted current (Iu)	1600 A
Rated uninterrupted current (Iu) at 50°C	1500 A
Rated uninterrupted current (Iu) at 60°C	1400 A
Rated uninterrupted current (Iu) at 70°C	1350 A
Rated short-time withstand current (t = 1 s)	42 kA
Overload release current setting - min	640 A
Overload release current setting - max	1600 A

Short-circuit release delayed setting - min		1200 A
Short-circuit release delayed setting - max		16000 A
Short-circuit release non-delayed setting		1.5 - 10 x I _r
Short-circuit release non-delayed setting - min		0 A
Short-circuit release non-delayed setting - max		24000 A
Adjustment range short-term delayed short-circuit release - min		960 A
Adjustment range short-term delayed short-circuit release - max		16000 A
Adjustment range undelayed short-circuit release - min		3200 A
Adjustment range undelayed short-circuit release - max		24000 A
Rated short-circuit breaking capacity at 400 V, 50 Hz		42 kA
Rated short-circuit making capacity up to 440 V, 50/60 Hz		88 kA
Rated short-circuit making capacity up to 690 V, 50/60 Hz		88 kA
Power of withdrawable switch with cassette		320 W
Closing delay via spring release		30 ms
Electrical connection type of main circuit		Rail connection
Number of standard mechanical operations per hour - max		60
Operating sequence up to 690 V, 50/60 Hz (IEC/EN 60947)		42 kA
Actuator type		Push button
Utilization category		B
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		10000 operations (switching capacity) 20000 operations (switching cycles ON/OFF, with maintenance)
Direction of incoming supply		As required
Technical Data - Mechanical		
Device construction		Built-in device slide-in technique (withdrawable)
Mounting Method		Withdrawable
Degree of protection		IP55 with protective cover IP31 with door seals IP31
Protection		P measurement
Number of auxiliary contacts (change-over contacts)		2
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Position of connection for main current circuit		Back side
Weight of cassette version (4-pole)		21 kg
Weight of fixed withdrawable version (4-pole)		33 kg
Lifespan, mechanical		12500 switching cycles (ON/OFF) 25000 operations (switching capacity, with maintenance)
Technical Data - Mechanical - Terminals		
Terminal capacity (copper bar)		5 mm x 100 mm (2x) for withdrawable units (black)
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (I _n)		1600 A
Equipment heat dissipation, current-dependent		320 W
Ambient operating temperature details		-20 °C - 70 °C
Ambient operating temperature - min		-20 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		-20 °C
Ambient storage temperature - max		70 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018])		
Rated permanent current I _u	A	1600
Rated voltage	V	690 - 690
Rated short-circuit breaking capacity I _{cu} at 400 V, 50 Hz	kA	42
Overload release current setting	A	640 - 1600
Adjustment range short-term delayed short-circuit release	A	960 - 16000
Adjustment range undelayed short-circuit release	A	3200 - 24000
Power loss	W	320
Device construction		Built-in device slide-in technique (withdrawable)
Integrated earth fault protection		No
Type of electrical connection of main circuit		Rail connection
Suitable for DIN rail (top hat rail) mounting		No
DIN rail (top hat rail) mounting optional		No
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		2
With switched-off indicator		Yes
With integrated under voltage release		No
Number of poles		4
Position of connection for main current circuit		Back side
Type of control element		Push button
Complete device with protection unit		Yes
Motor drive integrated		No
Motor drive optional		Yes
Degree of protection (IP)		IP31