DATASHEET - +IZMX-CAS404-2500-1



Cassette 2500A, IZMX404

Part no.

+IZMX-CAS404-2500-1 Catalog No. 183960



Delivery program

Donvoly program			
Product range			Accessories
Accessories			Withdrawable units
Accessories			Cassettes
			Equipment supplied: arcing chamber cover, terminal blocks fully wired as per electrical equipment
Rated current	In	Α	2500
Pole			4
For use with			IZMX404W INX404W
Instructions			With control circuit terminals according to ordered options.
Information about equipment supplied			with arcing chamber cover
Installation type			Withdrawable

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)					
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss10.0.1-27-37-04-22 [ACN955011])					
Rated current In	1	A	2500		
Number of poles			4		
Version as busbar adapter			No		
Version as built-in device			Yes		
Type of electrical connection of main circuit			Rail connection		

Dimensions

