

Surface mounting enclosure, Insulated material, With high-grade steel screws, Individually markable with pushbutton configurator, Number of locations 1, 1 x 30.5

Part no. **M30-FI1-***
197642

General specifications		
Product name		Eaton Moeller® series M30 Accessory Surface mounting enclosure
Part no.		M30-FI1-*
Product Length/Depth		110 millimetre
Product height		44 millimetre
Product width		43 millimetre
Product weight		0.095 kilogram
Certifications		CSA-C22.2 No. 14-05 UL File No.: E29184 CSA Class No.: 3211-03 IEC/EN 60947-5 CSA-C22.2 No. 94-91 CSA File No.: 012528 CSA certified CE marking UL Listed UL Category Control No.: NKCR UL 508
Product Tradename		M30
Product Type		Accessory
Product Sub Type		Surface mounting enclosure
Catalog Notes		Individually markable with pushbutton configurator
Features & Functions		
Enclosure color		Gray
Enclosure material		Plastic
Fitted with:		High-grade steel screws
Knockouts		1 x M20 (cable entry knockouts at the rear) 1 x M20 (cable entry knockout at the side)
Number of locations		1
RAL-number		7035
General information		
Degree of protection		NEMA 4X IP67/IP69K
Opening diameter		30 mm
Communication		
Connection to SmartWire-DT		No

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019])		
Number of command positions		1
Construction type housing		Surface mounted housing
Housing material		Plastic
Housing material quality		Other
Diameter openings	mm	30
Colour housing cover		Grey
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		4X
Width	mm	43
Height	mm	44
Depth	mm	110

