



Proximity switch, E57G General Purpose Serie, 1 NC, 3-wire, 10 - 30 V DC, M12 x 1 mm, S_n= 4 mm, Non-flush, PNP, Stainless steel, 2 m connection cable



Part no. E57G-12UPC4-C2
Catalog No. 197699
Alternate Catalog No. E57G-12UPC4-C2

Delivery program

Basic function			Inductive Sensors
Product range			E57G general purpose series
Connection			3-wire
Design (outer dimensions)		mm	M12 x 1
Rated operational voltage	U _e		10 - 30 V DC
Rated switching distance	S _n	mm	4
Type of mounting			Non-flush
Switching type			PNP
For connection of:			2 m connection cable
Contacts			
N/C = Normally closed			1 NC
Material			Stainless steel
Degree of Protection			IP67

Technical data

General

Standards			IEC/EN 60947-5-2
Ambient temperature			-25 - +70
Mechanical shock resistance		g	30 Shock duration 11 ms
Degree of Protection			IP67
Vibration			Amplitude 1 mm: 10 - 55 Hz

Characteristics

Rated switching distance			
Rated switching distance	S _n	mm	4
Repetition accuracy of S _n		%	3
Temperature drift of S _n		%	10
Switching hysteresis of S _n		%	20
Range		mm	4
Rated operational voltage	U _e		10 - 30 V DC
Maximum load current	I _e	mA	< 100
Operating current in the switched state at 24 V DC	I _b	mA	10
Voltage drop at I _e	U _d	V	2.5
Switching Frequency		Hz	2000
Response time		ms	200
Min. load current	I _e	mA	1
Switching state display		LED	Yellow
Protective functions			Short-circuit protective device
Connection			3-wire
Contacts			
N/C = Normally closed			1 NC
Style			
Design (outer dimensions)		mm	M12 x 1
For connection of:			2 m connection cable

Material		Stainless steel
----------	--	-----------------

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Sensors (EG000026) / Inductive proximity switch (EC002714)		
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Proximity switch / Inductive proximity switch (ecl@ss10.0.1-27-27-01-01 [AGZ376015])		
Width sensor	mm	0
Height of sensor	mm	0
Length of sensor	mm	64.1
Diameter sensor	mm	12
Mechanical mounting condition for sensor		Not flat
Switching distance	mm	4
Suitable for safety functions		No
Type of switch function		Breaker contact
Type of switching output		PNP
Type of electric connection		Cable
Number of semiconductor outputs with signalling function		1
Number of contact energized outputs with signalling function		0
Number of protected semiconductor outputs		0
Number of protected contact energized outputs		0
Type of actuation		Metallic Target
Type of interface		None
Type of interface for safety communication		None
Construction type housing		Cylinder, screw-thread
Coating housing		Other
Cascadable		No
Category according to EN 954-1		B
SIL according to IEC 61508		None
Performance level acc. EN ISO 13849-1		None
Max. output current at protected output	mA	0
Supply voltage	V	10 - 30
Rated control supply voltage Us at AC 50HZ	V	0 - 0
Rated control supply voltage Us at AC 60HZ	V	0 - 0
Rated control supply voltage Us at DC	V	10 - 30
Voltage type		DC
Switching frequency	Hz	2000
With monitoring function downstream switching devices		No
Material housing		Metal
Compression-resistant		No
Explosion safety category for gas		None
Explosion safety category for dust		None
Interference resistance to magnetic fields		

Approvals

Product Standards		UL 508/CSA-C22.2 No. 14
UL File No.		E166051
UL Category Control No.		NRKH, NRKH7
North America Certification		UL listed, certified by UL for use in Canada
Degree of Protection		UL Type 1

Additional product information (links)

IL053003EN Inductive sensors: E57 performance (short body), E57G General Purpose Series Inductive Proximity Sensors

IL053003EN Inductive sensors: E57 performance (short body), E57G General Purpose Series Inductive Proximity Sensors

ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL053003EN2018_10.pdf