

Insulated enclosure, HxWxD=280x200x125mm, +mounting rail



Part no. CI-K5-125-TS
206891
EL Number 4138005
(Norway)

General specifications		
Product name		Eaton Moeller® series CI-K Insulated enclosure
Part no.		CI-K5-125-TS
EAN		4015082068912
Product Length/Depth		280 millimetre
Product height		125 millimetre
Product width		200 millimetre
Product weight		0.91 kilogram
Certifications		UL94: HB IEC/EN 60529 UL94: V0/1.5 mm thickness IEC 60068-2-11 DIN EN 62208
Product Tradename		CI-K
Product Type		Insulated enclosure
Product Sub Type		None
Catalog Notes		Lamp indicator L... can be mounted in base knock-out M20/M25
Features & Functions		
Enclosure color		Light gray, Operator (RAL 7035) Light gray, Cover (RAL 7035) Black (RAL 9005)
Enclosure material		1 Ω x 10 ¹³ (Surface resistance to IEC 60093) Plastic
Features		Halogen free UV resistance beneath protective shield
Fitted with:		Mounting rail to IEC/EN 60715 Weight of fitted components: max. 0.65 kg Control cable entry
Knockouts		Hard knockout version Metric cable entry knockouts at the top, bottom and back plate
General information		
Cover material		Glass-fiber reinforced polycarbonate
Degree of protection		IP65 NEMA Other
Degree of protection (front side)		IP65
Dielectric strength		30 kV/mm, according to IEC 60243-1
Flammability characteristics		960 °C/1 mm thickness (base, cover; glow wire to VDE 0471 Part 2) 650 °C/1 mm thick (push-through membrane) to VDE 0471 Part 2)
Model		Surface mounting
Mounting depth		93 mm
Mounting weight capacity - max		1 kg
Product category		Empty enclosures
Suitable for		Emergency stop
Surface treatment		Resistant to corrosion
Track resistance		CTI 175 (base, to IEC 60112) CTI 175 (cover, to IEC 60112)
Type		Basic enclosure
Water consumption		0.29 % (According to DIN EN ISO 62)
Ambient conditions, mechanical		
Environmental resistance		Not resistant to benzene Resistant against greases Resistant against alkalis Chemical resistant (Push-through membrane (CI-K1/CI-K2) and sealing material) Resistant against mineral oil Partly resistant to alcohol Chemical resistant (Base, Cover)

		Partly resistant to greases Resistant against benzene Partly resistant to benzene Resistant against gasoline Resistant against acids (< 10%) Resistant against alcohol Resistant against salt solutions Partly resistant to acids (> 10%) Not resistant to alkalis Not resistant to Mineral oil
Impact resistance		IK06 (according to EN 50102)
Temperature resistance		-40 - 80 °C (gasket) -40 - 120 °C (enclosure)
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		35 W
Heat dissipation per pole, current-dependent P _{vid}		0 W
Rated operational current for specified heat dissipation (I _n)		0 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
Radiated heat dissipation with separate mounting		35 W (at an ambient temperature of 20 °C)
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Not applicable.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Meets the product standard's requirements.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss13-27-37-13-01 [AKN343019])		
Housing material		Plastic
Width	mm	200
Height	mm	125
Depth	mm	280
With transparent cover		No
Suitable for emergency stop		Yes
Model		Surface mounting

Degree of protection (IP)			IP65
Degree of protection (NEMA)			Other