

Insulated enclosure, HxWxD=240x160x125mm, +mounting plate



Part no. CI-K4-125-M
206897
EL Number 4138010
(Norway)

General specifications		
Product name		Eaton Moeller® series CI-K Insulated enclosure
Part no.		CI-K4-125-M
EAN		4015082068974
Product Length/Depth		240 millimetre
Product height		125 millimetre
Product width		160 millimetre
Product weight		1.01 kilogram
Certifications		IEC 60068-2-11 UL94: HB UL94: V0/1.5 mm thickness IEC/EN 60529 DIN EN 62208
Product Tradename		CI-K
Product Type		Insulated enclosure
Product Sub Type		None
Catalog Notes		Lamp indicator L-... can be mounted in base knock-out M20/M25
Features & Functions		
Enclosure color		Black (RAL 9005) Light gray, Cover (RAL 7035) Light gray, Operator (RAL 7035)
Enclosure material		1 Ω x 10 ¹³ (Surface resistance to IEC 60093) Plastic
Features		UV resistance beneath protective shield Halogen free
Fitted with:		Mounting plate Control cable entry
Knockouts		Metric cable entry knockouts at the top, bottom and back plate Hard knockout version
General information		
Cover material		Glass-fiber reinforced polycarbonate
Degree of protection		IP65 NEMA Other
Degree of protection (front side)		IP65
Dielectric strength		30 kV/mm, according to IEC 60243-1
Flammability characteristics		960 °C/1 mm thickness (base, cover; glow wire to VDE 0471 Part 2) 650 °C/1 mm thick (push-through membrane) to VDE 0471 Part 2)
Model		Surface mounting
Mounting depth		98 mm
Mounting weight capacity - max		0.9 kg
Product category		Empty enclosures
Suitable for		Emergency stop
Surface treatment		Resistant to corrosion
Track resistance		CTI 175 (cover, to IEC 60112) CTI 175 (base, to IEC 60112)
Type		Basic enclosure
Water consumption		0.29 % (According to DIN EN ISO 62)
Ambient conditions, mechanical		
Environmental resistance		Partly resistant to alcohol Chemical resistant (Push-through membrane (CI-K1/CI-K2) and sealing material) Resistant against alcohol Chemical resistant (Base, Cover) Not resistant to benzene Resistant against alkalis Partly resistant to greases Resistant against greases

			Resistant against salt solutions Not resistant to alkalis Partly resistant to benzene Resistant against gasoline Resistant against acids (< 10%) Partly resistant to acids (> 10%) Resistant against mineral oil Resistant against benzene Not resistant to Mineral oil
Impact resistance			IK06 (according to EN 50102)
Temperature resistance			-40 - 80 °C (gasket) -40 - 120 °C (enclosure)
Climatic environmental conditions			
Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Design verification			
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdis			26 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			0 W
Radiated heat dissipation with separate mounting			26 W (at an ambient temperature of 20 °C)
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Not applicable.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Meets the product standard's requirements.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Meets the product standard's requirements.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss13-27-37-13-01 [AKN343019])			
Housing material			Plastic
Width		mm	160
Height		mm	125
Depth		mm	240
With transparent cover			No
Suitable for emergency stop			Yes
Model			Surface mounting

Degree of protection (IP)			IP65
Degree of protection (NEMA)			Other