DATASHEET - K-CI-K1/2

Neutral terminal, for size K1/2

Part no.	K-CI-K1/2
	207451



Product name Eaton Moeller© series K-Cl Accessory Neutral terminal Part no. K-Cl-K1/2 EAN 4015082074517 Product Length/Depth 27 millimetre Product Neight 13 millimetre Product weight 0007 kilogram Product Weight 007 kilogram Product Tradename V/CSA crification not required Product Tradename Accessory Neutral terminal Product Nu Type Accessory Neutral terminal Product Nu Type Nutral terminal Product Autory Nutral terminal Accessory Neutral terminal Product Tradename Nutral terminal Product Type Accessory Neutral terminal Product Type Accessory Neutral terminal Product Type Nutral terminal Product Type Nutral terminal Functions Cornector of 5th conductor Product Category Connector Accessory Spare part type Connector Product Category Connector Anbient operating temperature - mina Straft Accessory Anbient operating temperature - max <td< th=""><th>General specifications</th><th></th></td<>	General specifications	
Parto. 64-642 EN 64-642 FNA 64-642 FNA 64-642 Podectarghtlyth 64-642 Podectarghtlythlyth 64-642 Podectarghtlythlythlythlythlythlythlythlythlythly		Esten Maellar® agrica K Cl Acagagan Neutral tarminal
FA415027617Product height (hight)21 millioriteProduct height (hight)21 millioriteProduct height (hight)20 millioniteProduct		
Product unplyUpphProduct unplyUpphProduct unplyUpphProduct unplyProduct unplyUSA set listic in the set of a set o		
ProductionI alimiteProductionI alimitesProductionI alimitesProduction		
Product width Image: Status in the image:		
Product weight Barker Science Device trained UCSA certification not required Product Type K-D Product Type Connection of a 5th confector Prod		
Definitions ULCSA certification not required Product Type KCI Product Type Accessory Product Sys Screwed onto support bases in the antiosure base plate Catalog Notes Connector Functions Connector of shb conductor Catalog Notes Connector Product Stapport Connector Product Stapport Connector Accessory Notes and Notes Connector Anderd operating tomperature - min Connector Termat Casparity Amin", fieldale Format Casparity Amin", fieldale Parimet Casparity Amin", fieldale Rest deproduct Standard's requirements. Amin", fieldale Rest deproduct Standard's requirements. Amin", fieldale Rest deproduct Standard's requirements.		
Product Tradename K-Cl Cataling Notes K-Cl	•	
Product Type Accessory Product Sub Type Accessory Catabo Notes Natrai terminal Catabo Notes Connection of sth conductor Functions Connection of sth conductor Catabo Notes Connection of sth conductor Functions Connection of sth conductor Catabo Notes Connector Accessory Visions part type Connector Catabo Notes Connector Anterior some particle some some some some some some some som		
Product Sab Type Readra Laminal Catalyo Nois Screweld and support boses in the exclosure base plate Functions Connection of a Sh conductor Catalyo Ny Same Connection of a Sh conductor Catalyo Ny Same Connection of a Sh conductor Catalyo Ny Same Connection Accessory Same part type Connector Product Sadowy Connector Catalyo Ny Same Connector Catalyo Ny Same Connector Catalyo Same Connector Anchiert operating temperature - max Connector Catalyo Same Connector Partification Connector Partification Connector Rest dissipation carent depender Pyoid O Heat dissipation carent depender Pyoid Connector Rest dissipation carent depender Pyoid Connector Rest dissipation or fersitation demaining matring instrong matrin demaining dissipation carent dyy since demain dy re	Product Tradename	K-CI
Cardon Norma Crewed onto support hosses in the enclosure base plate Functions Consector Cacesory/support type Consector Product category Consector Ambient operating temperature - min Consector Terminal capacity Consector Ratid displation, current dependent Pvid Consector Nation operating in marking system Consector Static bert dissignation, concurrent dependent Pvid Consector Nation capacity Profes Consector Nati		
entures & Functions processor connection of a 5h conductor Functions Connection of a 5h conductor Accessor/spare part type Connection of a 5h conductor Accessor/spare part type Connection Product catagory Ch K small inclosures Ambient operating tomperature - min Ch K small inclosures Ambient operating tomperature - max Ch K small inclosures Forminal capacities Ch K small inclosures Fast dissipation, current-dependent Pvid Ch K small inclosures Rate dissipation, non-current dependent Pvid V V Rate dissipation for subsing in matrials to normal heat Meets the product standard a requirements. 102.21 Wincitation of thermal stability of inclusure Meets the product standard a requirements. 102.22 Winfication of thermal stability of inclusure Meets the product standard a requirements. 102.23 Winfication of thermal stability of inclusure Meets the product standard a requirements.	Product Sub Type	Neutral terminal
Functions Connection of a 5th conductor Connection of a 5th conductor Connector Accessory spare part type Connector Product catagory Connector Instancio environmental conditions 40°C Antoint operating temperature - min 40°C Antoint operating temperature - max 40°C Ferminal capacities 40°C Ferminal capacities 0W Ferminal capacity environment-dependent Pvid 0W Hast dissipation per ople, current-dependent Pvid 0W Hast dissipation per ople, current-dependent Pvid 0W 102.22 Verification 22.4 102.23 Verification of testimate of insulating materials to normal heat Meets the product standard's requirements. 102.23 Verification of resistance of insulating material block effects Meets the product standard's requirements. 102.24 Verification of resistance of insulating material block effects Does not apply, since the errine switchgear needs to be evalated. 102.24 Verifi	Catalog Notes	Screwed onto support bosses in the enclosure base plate
Accessory/spare part type Connector Accessory/spare part type Connector Product cotopoy Cl-K small enclosures Ambient operating temporature - min Cl-K small enclosures Ambient operating temporature - min 40 °C Ambient operating temporature - min 40 °C Terminal capacities 40 °C Terminal capacity 40 °C Station for space from the dissipation, current-dependent Pvid W Head dissipation, non-current-dependent Pvid W Head dissipation, non-current-dependent Pvid Station of mersistance 102.23 Verification West the product standard's requirements. 102.24 wrification of terminal stability of enclosures Meets the product standard's requirements. 102.23 Verification of terminal stability of enclosures Meets the product standard's requirements. 102.24 wrification of terminal stability of enclosures Meets the product standard's requirements. 102.24 wrification of terminal colonylity of enclosures Meets the product standard's requirements. 102.24 wrification of usulting materials to normal heat Meets the product standard's requirements. 102.24 wrification of usulting materials to normal heat Meets the pr	Features & Functions	
Accessory spare part type Product category Froduct catego	Functions	Connection of a 5th conductor
Product caregory CLA small enclosures Climitic environmental conditions	General information	
Product caregory CLA small enclosures Climitic environmental conditions	Accessory/spare part type	Connector
Abient operating temperature - max 40 °C Ambient operating temperature - max 40 °C Terminal capacities 1-4 mm², flexible Terminal capacity 1-4 mm², flexible Design overfication 0V Equipment heat dissipation, current-dependent Pvid 0V Heat dissipation capacity Pdiss 22 A Static head dissipation, current-dependent Pvid 22 A Rated operational current for specified heat dissipation (In) 22 A Static head dissipation, current-dependent Pvid 0W 102.2 Oronsion resistance 0W 102.3 Verification of thermal stability of enclosures 0W 102.3 Verification of theird sispation (In) 24 Meets the product standard's requirements. 102.3 Verification of theird sispation (In) Meets the product standard's requirements. 102.3 Verification of theird sistability of enclosures Meets the product standard's requirements. 102.3 Verification of distance of insulating materials to normal heat Meets the product standard's requirements. 102.4 Meetshaightee, current distability of enclosures Meets the product standard's requirements. 102.5 Meetshaightee, current distability of enclosures Meets the product standard's requirements. 102.5 Meetshaightee,	Product category	CI-K small enclosures
Abient operating temperature - max 40 °C Ambient operating temperature - max 40 °C Terminal capacities 1-4 mm², flexible Terminal capacity 1-4 mm², flexible Design overfication 0V Equipment heat dissipation, current-dependent Pvid 0V Heat dissipation capacity Pdiss 22 A Static head dissipation, current-dependent Pvid 22 A Rated operational current for specified heat dissipation (In) 22 A Static head dissipation, current-dependent Pvid 0W 102.2 Oronsion resistance 0W 102.3 Verification of thermal stability of enclosures 0W 102.3 Verification of theird sispation (In) 24 Meets the product standard's requirements. 102.3 Verification of theird sispation (In) Meets the product standard's requirements. 102.3 Verification of theird sistability of enclosures Meets the product standard's requirements. 102.3 Verification of distance of insulating materials to normal heat Meets the product standard's requirements. 102.4 Meetshaightee, current distability of enclosures Meets the product standard's requirements. 102.5 Meetshaightee, current distability of enclosures Meets the product standard's requirements. 102.5 Meetshaightee,	Climatic environmental conditions	
Abbient operating temperature - max bein of periods reminal capacities Terminal capacity Terminal capa		-25 °C
Terminal capacities 1-4 mm ² , flexible Terminal capacity 1-4 mm ² , flexible Design verification 0W Equipment heat dissipation, current-dependent Pvid 0W Heat dissipation capacity Pdiss 0W Rated operational current for specified heat dissipation (In) 22 A Static heat dissipation, nor-current-dependent Pvid 0W 1022 Corrosion resistance 0W 1022.2 Vorffication of themal stability of enclosures 0W 1022.3 Vorffication of thesistance of insulating materials to normal heat Meets the product standard's requirements. 1022.3 Vorffication of tresistance of insulating materials to normal heat Meets the product standard's requirements. 102.3 X Vorffication of resistance of insulating materials to normal heat Meets the product standard's requirements. 102.3 X Vorffication of resistance of insulating materials to normal heat Meets the product standard's requirements. 102.3 X Vorffication of resistance of insulating materials to normal heat Meets the product standard's requirements. 102.4 Resistance to ultra-violat (UV) radiation Meets the product standard's requirements. 102.5 Uffig Does not apply, since the entire switchgear needs to be evaluated. 102.5 Intorpotion of a		
Teminal capacity 1 4 mm² flexible Design verification 0W Equipment heat dissipation, current-dependent Pvid 0W Heat dissipation capacity Pdiss 0W Rated operational current for specified heat dissipation (In) 32 A Static heat dissipation, non-current-dependent Pvid 0W 102.21 Verification of thermal stability of enclosures 0W 102.31 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.32 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 102.32 Verification of assemblies Meets the product standard's requirements. 102.32 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 102.32 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 102.32 Verification of resistance of insulating materials to normal heat Dees not apply, since the entire switchgear needs to be evaluated. 102.32 Verification of assemblies Dees not apply, since the entire switchgear needs to be evaluated. 103.24 Resistance to ultra-violet (UV) radiation Dees not apply, since the entire switchgear needs to be evaluated. 103.24 Resistance and creepage distances Meets the product		+0 0
Perign verification W Equipment heat dissipation, current-dependent Pvid W Heat dissipation papcity Pdiss W Heat dissipation prole, current-dependent Pvid W Rated operational current for specified heat dissipation (In) 32 A Static heat dissipation, non-current-dependent Pvis W 102.2 Corrosion resistance W 102.2.3 Uvrification of thermal stability of enclosures West she product standard's requirements. 102.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.3.2 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.3.2 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.3.2 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.4 Resistance to ultra-violet (UV) radiation Dees not apply, since the entire switchgear needs to be evaluated. 102.5 Uritions Dees not apply, since the entire switchgear needs to be evaluated. 10.5 Protection against electric shock Dees not apply, since the entire switchgear needs to be evaluated. 10.8 Coroporation of switchi		
Equipment heat dissipation, current-dependent Pvid 0 Heat dissipation capacity Pdiss 0 Heat dissipation prole, current-dependent Pvid 18.W Rated operational current for specified heat dissipation (In) 32.A Static heat dissipation, non-current-dependent Pvs 0W 102.2. Corrosion resistance 0W 102.2.1 Verification of thermal stability of enclosures 0W 102.2.3.1 Verification of nersistance of insulating materials to normal heat Meets the product standard's requirements. 102.2.3.2 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 102.4.1 Keisstance Does not apply, since the entire switchgear needs to be evaluated. 102.5.1 King Does not apply, since the entire switchgear needs to be evaluated. 102.5.1 King Does not apply, since the entire switchgear needs to be evaluated. 10.5.2 King Does not apply, since the entire switchgear needs to be evaluated. 10.5.2 King Does not apply, since the entire switchgear needs to be evaluated. 10.5.2 King Does not apply, since the entire switchgear needs to be evaluated. 10.5.2 King Does not apply, since the e		1 - 4 mm², flexible
Heat dissipation capacity Pdiss Heat dissipation capacity Pdiss Heat dissipation propele, current-dependent Pvid Rated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs U2.2 Corrosion resistance U2.2 Corrosion resistance U2.2 Strict chart dissipation of thermal stability of enclosures U2.2 Verification of thermal stability of enclosures U2.2 Verification of resistance of insulting materials to normal heat U2.2.3 Resist of insult, mat to abnormal heat/fire by internal elect. effects U2.4 Resistance to ultra-violet (UV) radiation U2.5 Lifting U2.5 Lifting U2.5 Lifting U2.5 Lifting U2.5 Lifting U3.5 Netction of assemblies U3.5 Resistance of protection of assemblies U3.5 Resistance of protection of assemblies U3.5 Protection against electric shock U3.5 Protection against electric shock U3.5 Protection against electric shock U3.5 Protection against electric and components U3.5 Protection against electric shock U3.5 Protection against electric and components U3.5 Protection against electric and connections U3.5 Pr	Design verification	
Heat dissipation per pole, current-dependent Pvid18 WRated operational current for specified heat dissipation (In)32 AStatic heat dissipation, non-current-dependent Pvs0 W10.2.2 Corrosion resistance0 W10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effectsMeets the product standard's requirements.10.2.4 Resistance to ultra-violet (UV) radiationDees not apply, since the entire switchgear needs to be evaluated.10.2.5 LiftingDees not apply, since the entire switchgear needs to be evaluated.10.2.6 Machanical impactDees not apply, since the entire switchgear needs to be evaluated.10.3.1 Portection of assembliesDees not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDees not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsStep panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder is responsibility.10.9.4 Testing of enclosures ma	Equipment heat dissipation, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)32 AStatic heat dissipation, non-current-dependent Pvs0W10.2.2 Corrosion resistance0W10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effectsMeets the product standard's requirements.10.2.4 Resistance to ultra-violet (UV) radiationMeets the product standard's requirements.10.2.5 LiftingDoes not apply, since the entire switchgear needs to be evaluated.10.2.6 Mechanical impactDoes not apply, since the entire switchgear needs to be evaluated.10.3.1 Segree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder is responsibility.10.01 Temperature riseIs the panel builder is responsibility.10.9.4 Testing of enclosures made of	Heat dissipation capacity Pdiss	0 W
Static heat dissipation, non-current-dependent Pvs0W10.2.2 Corrosion resistance0W10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effectsMeets the product standard's requirements.10.2.5 LiftingDoes not apply, since the entire switchgear needs to be evaluated.10.2.6 Mechanical impactDoes not apply, since the entire switchgear needs to be evaluated.10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder is responsibility.10.00 Temperature riseThe panel builder is responsibility.	Heat dissipation per pole, current-dependent Pvid	1.8 W
10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effectsMeets the product standard's requirements.10.2.4 Resistance to ultra-violet (UV) radiationMeets the product standard's requirements.10.2.5 LiftingDoes not apply, since the entire switchgear needs to be evaluated.10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.9.4 Testing of	Rated operational current for specified heat dissipation (In)	32 A
10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effectsMeets the product standard's requirements.10.2.4 Resistance to ultra-violet (UV) radiationDees not apply, since the entire switchgear needs to be evaluated.10.2.5 LiftingDees not apply, since the entire switchgear needs to be evaluated.10.2.6 Mechanical impactDees not apply, since the entire switchgear needs to be evaluated.10.3.0 Egree of protection of assembliesDees not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDees not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDees not apply, since the entire switchgear needs to be evaluated.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Inpulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder is responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder is responsibility.	Static heat dissipation, non-current-dependent Pvs	0 W
10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effectsMeets the product standard's requirements.10.2.4 Resistance to ultra-violet (UV) radiationDoes not apply, since the entire switchgear needs to be evaluated.10.2.5 LiftingDoes not apply, since the entire switchgear needs to be evaluated.10.2.6 Mechanical impactDoes not apply, since the entire switchgear needs to be evaluated.10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseThe panel builder's responsibility.	10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effectsMeets the product standard's requirements.10.2.4 Resistance to ultra-violet (UV) radiationDoes not apply, since the entire switchgear needs to be evaluated.10.2.5 LiftingDoes not apply, since the entire switchgear needs to be evaluated.10.2.6 Mechanical impactDoes not apply, since the entire switchgear needs to be evaluated.10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesDoes not apply, since the entire switchgear needs to be evaluated.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder is responsibility.10.10 Temperature riseThe panel builder is responsibility.	10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiationMeets the product standard's requirements.10.2.5 LiftingDoes not apply, since the entire switchgear needs to be evaluated.10.2.6 Mechanical impactDoes not apply, since the entire switchgear needs to be evaluated.10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.01 Temperature riseThe panel builder's responsibility.	10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.5 LiftingDoes not apply, since the entire switchgear needs to be evaluated.10.2.6 Mechanical impactDoes not apply, since the entire switchgear needs to be evaluated.10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseThe panel builder is responsibility.	10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.6 Mechanical impactDoes not apply, since the entire switchgear needs to be evaluated.10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseIt the panel builder's responsibility.	10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseThe panel builder is responsibility.	10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.3 Degree of protection of assembliesDoes not apply, since the entire switchgear needs to be evaluated.10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseThe panel builder is responsibility.	10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distancesMeets the product standard's requirements.10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialImpulse wither is responsibility.10.10 Temperature riseThe panel builder is responsible for the temperature rise calculation. Eaton will	10.2.7 Inscriptions	Meets the product standard's requirements.
10.5 Protection against electric shockDoes not apply, since the entire switchgear needs to be evaluated.10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseIt is panel builder is responsibility.	10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and componentsDoes not apply, since the entire switchgear needs to be evaluated.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseThe panel builder is responsible for the temperature rise calculation. Eaton will	10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.7 Internal electrical circuits and connectionsImage: Section of the panel builder's responsibility.10.8 Connections for external conductorsImage: Section of the panel builder's responsibility.10.9.2 Power-frequency electric strengthImage: Section of the panel builder's responsibility.10.9.3 Impulse withstand voltageImage: Section of the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialImage: Section of the panel builder's responsibility.10.10 Temperature riseImage: Section of the temperature rise calculation. Eaton will	10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.8 Connections for external conductors Is the panel builder's responsibility. 10.9.2 Power-frequency electric strength Is the panel builder's responsibility. 10.9.3 Impulse withstand voltage Is the panel builder's responsibility. 10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility. 10.10 Temperature rise Is the panel builder is responsibility.	10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseInterpanel builder's responsibility.	10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder's responsibility.10.9.4 Testing of enclosures made of insulating materialIs the panel builder's responsibility.10.10 Temperature riseImpulse with temperature rise calculation. Eaton will	10.8 Connections for external conductors	
10.9.3 Impulse withstand voltage Is the panel builder's responsibility. 10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will		
10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will		
10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will		

observed.	10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function The device meets the requirements, provided the information in the instruction	10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
leaflet (IL) is observed.	10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

 Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)

 Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Compo