EV busbars 1Ph., 6HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM



Part no. EVG-1PHAS/6MODUL 215638

General specifications	
Product name	Eaton Moeller series busbar
Part no.	EVG-1PHAS/6MODUL
EAN	9010238140356
Product Length/Depth	105 millimetre
Product height	35 millimetre
Product width	30 millimetre
Product weight	0.021 kilogram
Compliances	RoHS conform
Certifications	CE
Product Tradename	None
Product Type	Busbar
Product Sub Type	None
Product Specification Details	
Accessory/spare part type	Busbar for miniature circuit breaker Busbar for combined residual current/power circuit breaker Busbar for residual current circuit breakers
Color	Other
Cross section	10 mm ²
Electric connection type	Fork
Features	Insulated
Functions	Busbar
Number of modular spacings	6
Number of phases	1
Number of poles	Single-pole
Pitch dimensions	0 mm
Rated conditional short-circuit current (Iq)	25 kA
Rated operational voltage (Ue) - max	500 V
Rated short-time withstand current (Icw)	0 kA
Rated surge voltage	4 kV
Rated uninterrupted current (Iu)	63 A
Suitable for	6 devices
Suitable for number of devices	6
Туре	Busbar EVG
Used with	EVG Busbar

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)					
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])					
Number of phases			1		
Number of poles			1		
Suitable for number of devices			6		
Module width		mm	0		
Cross section		mm²	10		
Length		mm	105		
Can be cut to size			No		
Width in number of modular spacings			6		
Rated permanent current lu		Α	63		

Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current Iq	kA	25
Max. rated operation voltage Ue	V	500
Rated short-time withstand current lcw	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Other