

## Three-phase busbar link for 5 DILM7-12

**Part no.**                    **DILM12-XDSB0/5**  
**240086**

<b>General specifications</b>	
Product name	Eaton Moeller® series DILM three-phase busbar link
Part no.	DILM12-XDSB0/5
EAN	4015082400866
Product Length/Depth	202 millimetre
Product height	12 millimetre
Product width	25 millimetre
Product weight	0.07 kilogram
Certifications	UL File No.: E36332 CSA File No.: 012528 CE UL 508 UL Category Control No.: NLRV CSA Class No.: 2411-03 CSA-C22.2 No. 14-05 UL CSA IEC/EN 60947-4-1
Product Tradename	DILM
Product Type	Accessory
Product Sub Type	Three-phase busbar link
<b>Features &amp; Functions</b>	
Features	Insulated
Functions	Can be extended by rotating installation ( $\Sigma I_u \leq 35 \text{ A}$ )
Number of poles	Three-pole
Number of phases	3
Color	Black
Electric connection type	Pin
<b>General information</b>	
Product category	Accessories
<b>Climatic environmental conditions</b>	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	60 °C
<b>Electrical rating</b>	
Rated operational voltage (Ue) - max	690 V
Rated uninterrupted current (Iu)	35 A
<b>Short-circuit rating</b>	
Rated conditional short-circuit current (Iq)	0 kA
Rated short-time withstand current (Icw)	0 kA
<b>Design verification</b>	
Equipment heat dissipation, current-dependent Pvid	2.4 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0.8 W
Rated operational current for specified heat dissipation (In)	35 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ec!@ss13-27-37-13-06 [ACN992016])		
Number of phases		3
Number of poles		3
Suitable for number of devices		5
Module width	mm	45
Cross section	mm <sup>2</sup>	0
Length	mm	202
Can be cut to size		No
Width in number of modular spacings		11.2
Rated permanent current I <sub>u</sub>	A	35
Type of electric connection		Pin
Insulated		Yes
Rated surge voltage	kV	0
Conditioned rated short-circuit current I <sub>q</sub>	kA	0
Max. rated operation voltage U <sub>e</sub>	V	690
Rated short-time withstand current I <sub>cw</sub>	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Black