Off switch, 3p, 40A

Part no. ZP-A40/3

248265

**EL Number** 1457995

(Norway)



(1201774)	
General specifications	
Product name	Eaton Distribution parts
Part no.	ZP-A40/3
EAN	4015082482657
Product Length/Depth	80 millimetre
Product height	75 millimetre
Product width	54 millimetre
Product weight	0.282 kilogram
Compliances	RoHS conform
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes
Product Specification Details	
Built-in depth	60 mm
Color calotte	Other
Degree of protection	IP40
EL number	1457995
Imprint/indication	Symbol "arrows"
Lamp power	0 W
Lamp socket	Other
Lamp type	Other
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	3
Number of contacts (normally open contacts)	3
Number of poles	Three-pole
Rated operational voltage (Ue) - max	400 V
Rated short-time withstand current (Icw)	3 kA
Rated switching capacity	0 kA
Switch type	Off switch
Voltage rating - min	230 V
Voltage type	AC
Width in number of modular spacings	3

## **Technical data ETIM 9.0**

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss13-27-14-23-01 [AFZ813019])

Switching function			Off switch
Number of contacts as normally open contact			3
Number of contacts as normally closed contact			3
Number of contacts as change-over contact			0
Number of poles			3
Rated current	А		40
Rated voltage	V	,	400
Min. rated voltage	V	'	230

Rated switching capacity	kA	0
Short-circuit breaking capacity (Icw)	kA	3
Voltage type		AC
With signal lamp		No
Colour calotte		Other
Lamp type		Other
Lamp socket		Other
Max. lamp power	W	0
Width in number of modular spacings		3
Built-in depth	mm	60
Degree of protection (IP)		IP40
Imprint/indication		Symbol "arrows"
Forced segregation according to DIN VDE 0113		No