

Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS,
2W, 0.5HP

Part no. ZP-NHK

248437

EL Number

1609489

(Norway)

General specifications		
Product name		Eaton Distribution parts
Part no.		ZP-NHK
EAN		4015082484378
Product Length/Depth		80 millimetre
Product height		75 millimetre
Product width		8.8 millimetre
Product weight		0.044 kilogram
Compliances		RoHS conform
Certifications		UL Listed EN45545-2 IEC 61373
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Tripping signal contacts
Additional equipment required		Signaling switch
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for industrial and advanced commercial applications
Assembly width		0.5
Device fitting		Universal
EL number		1609489
Functions		Auxiliary switch
Number of contacts (change-over contacts)		2
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		0
Number of poles at main contact unit - max		2
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		250 V
Rated switch current		4 A
Suitable for current of main contact unit - max		4 A
Type		Accessory Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker
Used with		Auxiliary contacts Accessory Accessory for miniature circuit breaker Accessory for combined residual current/power circuit breaker
Voltage type		AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Universal

Function		Auxiliary switch
Width in number of modular spacings		0.5
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		2
Number of fault-signal switches		0
Rated switch current	A	4
Rated voltage	V	250
Voltage type		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	4