



RCD/RCB, 16A, 300mA, miniature circuit-breaker trip curve C, 1pole+N, residual current circuit-breaker trip characteristic: A

Part no. PKDM-16/1N/C/03-A
Catalog No. 248794

Similar to illustration

Delivery program

Basic function			Combined RCD/RCB devices
Number of poles			1 pole+N
Tripping characteristic			C
Application			Switchgear for residential and commercial applications
Rated current	I_n	A	16
Rated switching capacity according to IEC/EN 61009		kA	10
Rated fault current	$I_{\Delta N}$	A	0.3
Type			Type A
Tripping		s...	non-delayed
Product range			PKDM
Sensitivity			Pulse-current sensitive
Impulse withstand current			Partly surge-proof 250 A

Technical data

Electrical

Sensitivity			Pulse-current sensitive
-------------	--	--	-------------------------

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	16
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	3.6
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	40

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905)			
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / MCB/RCCB combination (ecl@ss10.0.1-27-14-22-07 [AFZ810015])			
Number of poles (total)			2
Number of protected poles			1
Rated voltage		V	230
Rated insulation voltage U_i		V	
Rated impulse withstand voltage U_{imp}		kV	
Rated current		A	16
Rated fault current		A	0.3
Leakage current type			A
Current limiting class			3
Rated short-circuit breaking capacity acc. EN 61009		kA	
Rated short-circuit breaking capacity IEC 60947-2		kA	0
Rated short-circuit breaking capacity I_{cn} acc. EN 61009-1		kA	
Disconnection characteristic			
Surge current capacity		kA	0.25

Voltage type			AC
Frequency			50 Hz
Release characteristic			C
Concurrently switching N-neutral			Yes
With interlocking device			
Over voltage category			3
Pollution degree			2
Ambient temperature during operating		°C	
Width in number of modular spacings			2
Built-in depth		mm	69.5
Suitable for flush-mounted installation			No
Anti-nuisance tripping version			No
Degree of protection (IP)			IP20
Connectable conductor cross section solid-core		mm ²	
Connectable conductor cross section multi-wired		mm ²	