

Auxiliary contact, for FI..., 1W+1N/C, 0.5HP

Part no. **FIPA-XAM011**
262578

General specifications		
Product name		Eaton Distribution parts
Part no.		FIPA-XAM011
EAN		4015082625788
Product Length/Depth		62 millimetre
Product height		75 millimetre
Product width		9 millimetre
Product weight		0.06 kilogram
Compliances		RoHS conform
Certifications		EN45545-2 IEC 61373
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Auxiliary contacts
Additional equipment required		Other
Admissible back-up fuse - max		6 A gL
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Assembly width		0.5
Contact function		1 C/O + 1 B
Degree of protection		IP40
Device fitting		Universal
Enclosure width		90 mm
Frame		Standard front dimension: 45 mm
Frequency rating		50 Hz / 60 Hz
Functions		Auxiliary switch
Mounting width		8.8 mm (0.5 space units)
Number of contacts (change-over contacts)		1
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		0
Number of poles at main contact unit - max		2
Number of switches (fault signal)		0
Rated insulation voltage (Ui)		440 V AC
Rated operational current		1 A (230 V DC-11) 6 A (230 V AC-11)
Rated operational voltage (Ue) - max		230 V
Rated switch current		3 A
Special features		IP20 (switch)
Suitable for current of main contact unit - max		0 A
Terminal capacity (cable)		2.5 mm ²
Terminal capacity (solid wire)		2.5 mm ²
Terminal protection		Protection against electric shock to IEC 536
Terminal type		Twin-purpose terminals
Type		Accessory Accessory for residual current circuit breaker

Used with		Accessory Accessory for residual current circuit breaker
Voltage type		AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Universal
Function		Auxiliary switch
Width in number of modular spacings		0.5
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		1
Number of fault-signal switches		0
Rated switch current	A	3
Rated voltage	V	230
Voltage type		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	0