

Auxiliary contact, for PFDM, 1W+1N/C, 0.5HP



**Part no.**                      **Z-HD**  
**265620**

| <b>General specifications</b>                   |  |   |
|---|--|---|
| Product name                                    |  | Eaton Distribution parts  |
| Part no.  |  | Z-HD  |
| EAN   |  | 4015082656201   |
| Product Length/Depth                            |  | 88 millimetre   |
| Product height                                  |  | 75 millimetre   |
| Product width                                   |  | 22 millimetre   |
| Product weight                                  |  | 0.043 kilogram  |
| Compliances                                     |  | RoHS conform  |
| Certifications                                  |  | EN45545-2<br>IEC 61373  |
| Product Tradename                               |  | None  |
| Product Type                                    |  | Distribution parts  |
| Product Sub Type                                |  | None  |
| Public Consumption                              |  | Yes   |
| Product Family Description                      |  | ES-PMCC-PDC-Eaton Distribution parts  |
| Globally Marketable                             |  | Yes   |
| <b>Product Specification Details</b>            |  |   |
| Accessory/spare part type                       |  | Auxiliary contacts  |
| Additional equipment required                   |  | Auxiliary switch  |
| Ambient operating temperature - max             |  | 40 °C   |
| Ambient operating temperature - min             |  | -5 °C   |
| Application                                     |  | Switchgear for industrial and advanced commercial applications                    |
| Assembly width                                  |  | 0.5   |
| Device fitting                                  |  | Earth leakage switch  |
| Functions                                       |  | Auxiliary switch  |
| Number of contacts (change-over contacts)       |  | 1   |
| Number of contacts (normally closed contacts)   |  | 1   |
| Number of contacts (normally open contacts)     |  | 0   |
| Number of poles at main contact unit - max      |  | 2   |
| Number of switches (fault signal)               |  | 0   |
| Rated operational voltage (Ue) - max            |  | 230 V   |
| Rated switch current                            |  | 3 A   |
| Suitable for current of main contact unit - max |  | 6 A   |
| Type  |  | Accessory<br>Accessory for residual current circuit breaker                       |
| Used with                                       |  | Auxiliary contacts<br>Accessory<br>Accessory for residual current circuit breaker |
| Voltage type                                    |  | AC  |

**Technical data ETIM 9.0**

|   |  |                      |
|---|--|----------------------|
| Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)  |  |                      |
| Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018]) |  |                      |
| Device fitting  |  | Earth leakage switch |
| Function  |  | Auxiliary switch     |
| Width in number of modular spacings   |  | 0.5                  |
| Number of contacts as normally open contact   |  | 0                    |
| Number of contacts as normally closed contact   |  | 1                    |
| Number of contacts as change-over contact   |  | 1                    |

|   |   |     |
|---|---|-----|
| Number of fault-signal switches                             |   | 0   |
| Rated switch current  | A | 3   |
| Rated voltage   | V | 230 |
| Voltage type  |   | AC  |
| With auto test for earth leakage function                   |   | No  |
| Suitable for max. number of poles main contact unit (total) |   | 2   |
| Suitable for max. current main contact unit                 | A | 6   |