

Busbar, isolated, 63A, 3p, 4Mod



Part no. Z-GV-10/3P-4TE
271080
EL Number 1657135
(Norway)

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-GV-10/3P-4TE
EAN		4015082710804
Product Length/Depth		25.5 millimetre
Product height		14.9 millimetre
Product width		965 millimetre
Product weight		0.406 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Color		Other
Cross section		10 mm ²
EL number		1657135
Electric connection type		Fork
Features		Insulated Can be cut to size
Number of modular spacings		5
Number of phases		3
Number of poles		Three-pole
Pitch dimensions		0 mm
Rated conditional short-circuit current (Iq)		0 kA
Rated operational voltage (Ue) - max		415 V
Rated short-time withstand current (Icw)		0 kA
Rated surge voltage		0 kV
Rated uninterrupted current (Iu)		0 A
Suitable for		Devices with auxiliary switch
Suitable for number of devices		39

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ec@ss13-27-37-13-06 [ACN992016])		
Number of phases		3
Number of poles		3
Suitable for number of devices		39
Module width	mm	0
Cross section	mm ²	10
Length	mm	25.5
Can be cut to size		Yes
Width in number of modular spacings		5
Rated permanent current Iu	A	0
Type of electric connection		Fork

Insulated		Yes
Rated surge voltage	kV	0
Conditioned rated short-circuit current Iq	kA	0
Max. rated operation voltage Ue	V	415
Rated short-time withstand current Icw	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		Yes
Colour		Other