



**Phase busbar, 4-phases, 10qmm, fork connector+pin, 12SU**

**Part no. Z-GSV-10/3P+N/12-U**  
**Catalog No. 274400**

Similar to illustration

## Technical data ETIM 7.0

| Low-voltage industrial components (EG000017) / Phase busbar (EC000215)  |  |                 |       |
|---|--|-----------------|-------|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ec@ss10.0.1-27-37-13-06 [ACN992011]) |  |                 |       |
| Number of phases  |  |                 | 4     |
| Number of poles   |  |                 | 3     |
| Suitable for number of devices  |  |                 | 9     |
| Pitch dimensions  |  | mm              | 17.95 |
| Cross section   |  | mm <sup>2</sup> | 10    |
| Length  |  | mm              | 215   |
| Number of modular spacings  |  |                 | 12    |
| Rated permanent current I <sub>u</sub>  |  | A               | 50    |
| Type of electric connection   |  |                 | Other |
| Insulated   |  |                 | Yes   |
| Rated surge voltage   |  | kV              | 0     |
| Conditioned rated short-circuit current I <sub>q</sub>  |  | kA              | 25    |
| Max. rated operation voltage U <sub>e</sub>   |  | V               | 415   |
| Rated short-time withstand current I <sub>cw</sub>  |  | kA              | 0     |
| Suitable for devices with N-busbar  |  |                 | Yes   |
| Suitable for devices with auxiliary switch  |  |                 | No    |