



Pushbutton with LED, 24AC/DC, 2N/O, 16A, orange, 1HP

Part no. Z-PUL24/SS
 Catalog No. 276295

Similar to illustration

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	16
Heat dissipation per pole, current-dependent	P_{vid}	W	2
Equipment heat dissipation, current-dependent	P_{vid}	W	4

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Push button for distribution board (EC001546)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Push button for distribution board (ec1@ss10.0.1-27-14-23-02 [AFZ814014])			
Number of contacts as normally closed contact			0
Number of contacts as normally open contact			2
Number of contacts as change-over contact			0
Switching current		A	16
Switching voltage		V	250
Voltage type			AC
With signal lamp			Yes
Colour calotte			Not applicable
Lamp type			LED
Lamp socket			Other
Max. lamp power		W	2
Lamp voltage		V	12 - 24
Colour button			Green
Width in number of modular spacings			1
Built-in depth		mm	60
Degree of protection (IP)			IP40