

Pushbutton with LED, 230AC/DC, 2N/O, 16A, orange, 1HP



Part no. **Z-PUL230/SS**
276297

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-PUL230/SS
EAN		4015082762971
Product Length/Depth		80 millimetre
Product height		70 millimetre
Product width		17.5 millimetre
Product weight		0.08 kilogram
Compliances		RoHS conform
Certifications		CE
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Actuator color		Green
Built-in depth		60 mm
Color calotte		Other
Degree of protection		IP40
Equipment heat dissipation, current-dependent		4 W
Fitted with:		Signal lamp
Heat dissipation per pole, current-dependent		2 W
Lamp power		2 W
Lamp socket		Other
Lamp type		LED
Lamp voltage - max		240 V
Lamp voltage - min		110 V
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		2
Rated operational current for specified heat dissipation (In)		16 A
Switching current		16 A
Switching voltage		250 V
Used with		Enclosure 1000 x 600 mm
Voltage type		AC
Width in number of modular spacings		1

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Push button for distribution board (EC001546)		
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Push button for distribution board (ec@ss13-27-14-23-02 [AFZ814019])		
Number of contacts as normally closed contact		0
Number of contacts as normally open contact		2
Number of contacts as change-over contact		0
Switching current	A	16
Switching voltage	V	250
Voltage type		AC

With signal lamp			Yes
Colour calotte			Other
Lamp type			LED
Lamp socket			Other
Max. lamp power		W	2
Lamp voltage		V	110 - 240
Colour button			Green
Width in number of modular spacings			1
Built-in depth		mm	60
Degree of protection (IP)			IP40