

Switch with LED, 230AC/DC, 1N/O+1N/C, 16A, orange, 1HP



Part no. **Z-SWL230/SO**
276307

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-SWL230/SO
EAN		4015082763077
Product Length/Depth		80 millimetre
Product height		70 millimetre
Product width		17.5 millimetre
Product weight		0.065 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Built-in depth		80 mm
Color calotte		Other
Degree of protection		IP40
Equipment heat dissipation, current-dependent		4 W
Fitted with:		Signal lamp
Heat dissipation per pole, current-dependent		2 W
Inscription		Other
Lamp power		2 W
Lamp socket		Other
Lamp type		LED
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles		Two-pole
Rated operational current for specified heat dissipation (In)		16 A
Rated operational voltage (Ue) - max		250 V
Rated short-time withstand current (Icw)		0.02 kA
Switch type		Control switch
Voltage rating - min		230 V
Voltage type		AC
Width in number of modular spacings		1

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)		
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss13-27-14-23-01 [AFZ813019])		
Switching function		Control switch
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of poles		2
Rated current	A	16
Rated voltage	V	250

Min. rated voltage	V	230
Rated switching capacity	kA	0.016
Short-circuit breaking capacity (Icw)	kA	0.02
Voltage type		AC
With signal lamp		Yes
Colour calotte		Other
Lamp type		LED
Lamp socket		Other
Max. lamp power	W	2
Width in number of modular spacings		1
Built-in depth	mm	80
Degree of protection (IP)		IP40
Imprint/indication		Other
Forced segregation according to DIN VDE 0113		No