

Module plate, 2-hole, vertical, 3p, 1250A

Part no. **NZM4-XKM2S-1250**
284471

General specifications		
Product name		Eaton Moeller series NZM connection type
Part no.		NZM4-XKM2S-1250
EAN		4015082844714
Product Length/Depth		108 millimetre
Product height		12 millimetre
Product width		150 millimetre
Product weight		1.432 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		CSA (File No. 22086) CSA certified CE marking UL (Category Control Number DIHS) IEC60947 CSA-C22.2 No. 5-09 UL (File No. E31593) UL489 CSA (Class No. 1432-01) UL listed
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Connection type
Delivery program		
Type		Accessory Module plate Terminal
Number of poles		Three-pole
Amperage Rating		≤ 1250 A
Special features		Two holes
Frame		NZM4
Suitable for		Copper cable lugs Three-pole
Used with		NZM4, N(S)4
Technical Data - Mechanical		
Special features		Two holes
Technical Data - Mechanical - Terminals		
Terminal capacity (flexible cable)		95 mm ² - 300 mm ² (2x) Max. 600 AWG/kcmil (2x)
Terminal capacity (copper busbar)		50 mm x 10 mm (2x) 40 mm x 10 mm (2x)
Terminal capacity (copper strip)		10 segments of 50 mm x 1 mm (2x) 10 segments of 40 mm x 1 mm (2x)
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecI@ss13-27-37-13-05 [ACN990017])			
Suitable for number of poles			3