

Power incoming cable, flat cable, L=1.5m



Part no. RA-C3/C1-1,5HF
290210

Product name	Eaton Moeller® series Rapid Link Accessory Power adapter cable
Part no.	RA-C3/C1-1,5HF
EAN	4015082902100
Product Length/Depth	1.5 metre
Product height	50 millimetre
Product width	240 millimetre
Product weight	0.429 kilogram
Compliances	CE
Product Tradename	Rapid Link
Product Type	Accessory
Product Sub Type	Power adapter cable
Color	Gray
Features	Connector system system-oriented Oil resistant (acc. EN 60811-404)
Fitted with:	Power plug and plug for flexible busbar junction, halogen-free, 5 x 1.5 mm ² Protective conductor
Functions	For connecting the device with the 400 V AC flexible busbar junction
Degree of protection	Other
Nominal current	6.6 A
Nominal voltage - min	480 V
Nominal voltage - max	480 V
Product category	Power supply
Permissible ambient temperature - min	-10 °C
Permissible ambient temperature - max	55 °C
Outer diameter - approximate	10 mm
Outer sheath material	Other

Technical data ETIM 8.0

Batteries, chargers and power cords (EG000053) / Power cord (EC001576)		
Electric engineering, automation, process control engineering / Cable, wire / Ready-made low-voltage line / Extension line (low-voltage line) (ecl@ss10.0.1-27-06-04-02 [AAB665013])		
Connection 1		Other
Connection 2		Other
Connector system system-oriented		Yes
Number of cores		5
Nominal cross section conductor	mm ²	1.5
Length	m	1.5
Material outer sheath		Other
Temperature resistance	°C	-10 - 55
Nominal current	A	6.6
Nominal voltage	V	480 - 480
Frequency	Hz	50 - 60
Colour outer sheath		Grey
Spiralized cable		No
With protective conductor		Yes
Degree of protection (IP)		Other

Oil resistant (according to EN 60811-404)		Yes
With cord switch		No
Outer diameter approx.	mm	10
Reaction-to-fire class according to EN 13501-6		None
Smoke development class according to EN 13501-6		None
Euro class flaming droplets/particles according to EN 13501-6		None
Euro class acidity according to EN 13501-6		None