



EV busbars 2Ph., 4HP, 80A for PLS. CLS. PKN., PFIM, PFHM, PFNM

Part no. EVG-16/2PHAS/4MODUL
Catalog No. 291467

Similar to illustration

Delivery program

Basic function		Busbar
Basic function accessories		Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker
Busbar type		2 phase
Product range		EVG

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011])

Number of phases		2
Number of poles		2
Suitable for number of devices		2
Pitch dimensions	mm	0
Cross section	mm ²	16
Length	mm	71.2
Number of modular spacings		4
Rated permanent current I _u	A	80
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current I _q	kA	25
Max. rated operation voltage U _e	V	415
Rated short-time withstand current I _{cw}	kA	0
Suitable for devices with N-busbar		No
Suitable for devices with auxiliary switch		No

Dimensions

