

Busbar AUX 1p+AUX long pin



Part no. **Z-VPL-4/1p+HS**  
**302376**

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-VPL-4/1p+HS
EAN		9010238159341
Product Length/Depth		1000 millimetre
Product height		27.5 millimetre
Product width		4.5 millimetre
Product weight		0.09 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Color		Grey
Cross section		4 mm <sup>2</sup>
Electric connection type		Pin
Features		Insulated Can be cut to size
Number of modular spacings		38
Number of phases		1
Number of poles		Single-pole
Pitch dimensions		17 mm
Rated conditional short-circuit current (I <sub>q</sub> )		0 kA
Rated operating voltage (U <sub>e</sub> ) - max		1500 V
Rated short-time withstand current (I <sub>cw</sub> )		0 kA
Rated surge voltage		0 kV
Rated uninterrupted current (I <sub>u</sub> )		32 A
Suitable for		38 devices

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])		
Number of phases		1
Number of poles		1
Suitable for number of devices		38
Module width	mm	17
Cross section	mm <sup>2</sup>	4
Length	mm	1000
Can be cut to size		Yes
Width in number of modular spacings		38
Rated permanent current I <sub>u</sub>	A	32
Type of electric connection		Pin
Insulated		Yes
Rated surge voltage	kV	0
Conditioned rated short-circuit current I <sub>q</sub>	kA	0

Max. rated operation voltage U <sub>e</sub>	V	1500
Rated short-time withstand current I <sub>cw</sub>	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Grey