



Eaton 5S 700i

**Part no.
Catalog No.**

**Eaton 5S 700i
5S700I**

Delivery program

| | | |
|---------------|--|-----|
| Product range | | UPS |
|---------------|--|-----|

Technical data ETIM 7.0

| | | |
|--|-----|-----------------------------|
| Data and telecommunication (EG000037) / UPS (EC000382) | | |
| Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ec1@ss10.0.1-27-04-06-90 [BAB258012]) | | |
| Input voltage | V | 175 - 275 |
| Primary frequency | Hz | 50 - 60 |
| Number of phases primary | | 1 |
| Output voltage | V | 230 - 230 |
| Secondary frequency | Hz | 50 - 60 |
| Output effective power | W | 420 |
| Output apparent power | VA | 700 |
| Type of interface | | USB |
| Number of phases secondary | | 1 |
| SNMP | | No |
| Voltage type | | AC |
| Height | mm | 250 |
| Width | mm | 87 |
| Depth | mm | 260 |
| Transition time for full load | min | 2 |
| Weight | kg | 5.98 |
| Network-management | | No |
| USV- technology | | Line-interactive |
| Construction type | | Free standing model |
| Max. voltage distortion output (linear load) | % | 0 |
| Output power factor | | 0.6 |
| Overall efficiency | % | 95 |
| Efficiency in eco-mode | % | 95 |
| Potential free switch contact | | No |
| Auto shut down function | | Yes |
| Input connection | | Protective contact (SCHUKO) |
| Number of output connections C13 | | 6 |
| Number of output connections C19 | | 0 |
| Number of output connections with protective contact (SCHUKO) | | 0 |
| Number of output connections fixed connection | | 0 |