



**EATON 5SC 500i**

**Part no.  
Catalog No.**

**Eaton 5SC 500i  
5SC500I**

### Delivery program

Product range		UPS
---------------	--	-----

### Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	184 - 276
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	220 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	350
Output apparent power	VA	500
Type of interface		Other
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	210
Width	mm	150
Depth	mm	240
Transition time for full load	min	5
Weight	kg	6.6
Network-management		No
USV- technology		Line-interactive
Construction type		Free standing model
Max. voltage distortion output (linear load)	%	0
Output power factor		0.7
Overall efficiency	%	94
Efficiency in eco-mode	%	94
Potential free switch contact		No
Auto shut down function		Yes
Input connection		C14
Number of output connections C13		4
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		0