



Fuse-link, low voltage, 60 A, AC 600 V, DC 250 V, 200 kA, HRCII-C, 22 x 87 mm, CSA

Part no. **60A 600V AC BRUSH FUSE CANADA**  
 Catalog No. **60K07C**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	60
Rated voltage			AC 600 V DC 250 V
Construction size			HRCII-C
Size			22 x 87 mm
Breaking Capacity		kA	200
usable for size/applications			Cable protection
Standard/Approval			CSA
Shape			offset bolted tags
Standards/Regulations			CSA C22.2 No. 106-M1992

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	60
Rated voltage		V	600
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

### Additional product information (links)

Product datasheet (web)	<a href="http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/iec_british0/hrc_form_ii_current-limitingfuses1.html">http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/iec_british0/hrc_form_ii_current-limitingfuses1.html</a>
-------------------------	---