



Fuse-link, LV, 6 A, AC 500 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs

EL Number (Norway)
6NHG000B
1664002

| | | |
|--------------------------------------|--|---|
| Product name | | Eaton Busmann series low voltage NH Fuse |
| Part no. | | NH FUSE 6A 500V SIZE 000 GG MGL |
| EAN | | 5027590486323 |
| Product Length/Depth | | 79 millimetre |
| Product height | | 51 millimetre |
| Product width | | 21 millimetre |
| Product weight | | 131 gram |
| Compliances | | CE Marked RoHS Compliant |
| Certifications | | IEC 60269-2 IEC 60269-1 DIN 43620 |
| Product Tradename | | None |
| Product Type | | Low voltage NH fuse |
| Product Sub Type | | None |
| Amperage Rating | | 6 A |
| Voltage rating | | 500 V |
| Voltage type | | AC |
| Breaking capacity | | 120 kA |
| Class | | Class gG/gL |
| Frequency rating - min | | 45 Hz |
| Frequency rating - max | | 62 Hz |
| Fuse size | | NH000 |
| Insulated metal gripping lugs (IMGL) | | No |
| Suitable for | | Microswitch 170H0236 EBF Vertical fuse rail EBV Vertical fuse switch-disconnectors EBH Size 000 Horizontal fuse switch-disconnectors |

Technical data ETIM 8.0

| | | |
|---|----|---|
| Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | |
| Fuse construction type according to IEC 60269 | | NH000 |
| Voltage type | | AC |
| Rated current | A | 6 |
| Rated voltage AC | V | 500 |
| Rated voltage DC | V | |
| Rated switching capacity | kA | 120 |
| Utilization category | | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator | | Combination fuse status indicator |
| Insulated metal gripping lugs (IMGL) | | No |
| Power loss at rated current | W | 2 |