



Fuse-link, LV, 25 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS

**AA025**

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse	
Part no.	AA025	
EAN	5027590491549	
Product Length/Depth	85 millimetre	
Product height	14 millimetre	
Product width	14 millimetre	
Product weight	20.1 gram	
Compliances	RoHS Compliant	
Product Tradename	None	
Product Type	Low voltage British standard fuse	
Product Sub Type	None	
Amperage Rating	25 A	
Voltage rating	550 V	
Voltage type	AC	
Breaking capacity	80 kA	
Class	Class gG/gL	
Application	general industrial applications	
Fuse type	AA0	
Fuse size	BS88/A2	
Fitted with:	Offset bolted tags	
Connection	73 mm fixing centre	
Quantity	20	
Suitable for	CM32F Camaster fuse holder RS32 Red spot fuse holder	

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A2
Type of current		AC
Rated voltage AC	V	550
Rated voltage DC	V	
Rated current	A	25
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	2.1
Mounting holes		
Centre-to-centre distance of connections	mm	73