



Fuse-link, LV, 12 A, AC 690 V, 14 x 51 mm, gL/gG, IEC

**EL Number  
(Norway)**

**C14G12  
1600236**

Similar to illustration

Product name	Eaton Busmann series low voltage cylindrical fuse
Part no.	C14G12
EAN	5027590493826
Product Length/Depth	51 millimetre
Product height	14.3 millimetre
Product width	14.3 millimetre
Product weight	20.3 gram
Compliances	RoHS Compliant GoST-R CE Marked
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	12 A
Voltage rating	690 V
Voltage type	AC
Breaking capacity	80 kA
Utilization category	gL/gG (cable protection/equipment protection)
Suitable for	CH14 Modular fuse holder

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		14x51 mm
Voltage type		AC
Rated current	A	12
Rated voltage	V	690
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	80
Power loss at rated current	W	1.7