



Fuse-link, LV, 50 A, AC 400 V, 14 x 51 mm, gL/gG, IEC, with striker

**C14G50S**

Product name		Eaton Bussmann series low voltage cylindrical fuse
Part no.		C14G50S
EAN		5027590494144
Product Length/Depth		51 millimetre
Product height		14 millimetre
Product width		14 millimetre
Product weight		20.4 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269
Product Tradename		None
Product Type		Low voltage cylindrical fuse
Product Sub Type		None
Amperage Rating		50 A
Voltage rating		400 V
Voltage type		AC
Breaking capacity		120 kA
Utilization category		gG (cable protection/equipment protection)
Suitable for		CH14 Modular fuse holder

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		14x51 mm
Voltage type		AC
Rated current	A	50
Rated voltage	V	400
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Top fuse status indicator
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	4.8