



**Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 2XIEC60309 32A 3P**



**Catalog No. EILB26**

Similar to illustration

## Delivery program

Type		Rack PDU
Input Connection		2 x IEC-60309 32A 3Ph
Cord Length		3m
Input Voltage		346-415V
Phase		Three-phase
Frequency Rating		50/60 Hz
Ethernet Interface		Yes
Serial Interface		Yes
Form Factor		0U (Vertical)
Outlet Control		No
Operating Temperature		0° to 60°C (32° to 140°F)
Outlets		2XIEC60309 32A 3P
Number of Outputs C13		0
Number of Outputs C19		0
Amperage Rating		32A
Mounting Direction		Vertical
ETIM Class		EC002762
Fitted With:		Display Mounting material Ampere Meter
Electrical Connection		Connecting cord with plug
Evaluation		At distance
Mounting Dimension (metrical)		52
Mounting Dimension (standardised)		Metric
Switchable		No
Over Voltage Category		2
Wattage		22 kW max
Communication		HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP		Yes
Mass Configuration		Yes
Package Contents		PDU, Mounting accessories, Network cable, Configuration cable, Splitter for daisy-chaining, Quickstart guide, Safety Instructions
Number of Outputs C20		0
Num of Outputs PC (SCHUKO)		0
Number of Outputs (Other)		2
Number of Outlets with Earth Pin		2
Color		Black

## Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ec@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		Metric
Mounting dimension	mm	52
Mounting direction		Vertical
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	3
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		2
Number of C13 socket outlets		0
Number of C19 socket outlets		0
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		2
Number of height units		0
Length	mm	439
Width	mm	65
Height	mm	52
Depth	mm	439
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes