



Eaton Ellipse PRO 650 IEC

Part no.

Eaton Ellipse PRO 650 IEC

Catalog No.

ELP650IEC

Delivery program

Product range	UPS
---------------	-----

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)			
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss10.0.1-27-04-06-90 [BAB258012])			
Input voltage	V	165 - 285	
Primary frequency	Hz	50 - 60	
Number of phases primary		1	
Output voltage	V	220 - 240	
Secondary frequency	Hz	50 - 60	
Output effective power	W	400	
Output apparent power	VA	650	
Type of interface		USB	
Number of phases secondary		1	
SNMP		No	
Voltage type		AC	
Height	mm	260	
Width	mm	82	
Depth	mm	285	
Transition time for full load	min	1	
Weight	kg	6.6	
Network-management		No	
USV- technology		Line-interactive	
Construction type		482.6 mm (19 inch) device	
Max. voltage distortion output (linear load)	%	0	
Output power factor		0.6	
Overall efficiency	%	95	
Efficiency in eco-mode	%	95	
Potential free switch contact		No	
Auto shut down function		Yes	
Input connection		Protective contact (SCHUKO)	
Number of output connections C13		4	
Number of output connections C19		0	
Number of output connections with protective contact (SCHUKO)		0	
Number of output connections fixed connection		0	