

EPDU MA 1U (C20 16A 1P)8XC13



Catalog No. EMAH28

Similar to illustration

| livery program | |
|---------------------------------------|---|
| , program | |
| Туре | Rack PDU |
| | C20 |
| Input Connection | |
| Cord Length | 3m |
| Input Voltage | 200-240V |
| Phase | Single-phase |
| Frequency Rating | 50/60 Hz |
| Ethernet Interface | Yes |
| Serial Interface | Yes |
| Form Factor | 1U |
| Outlet Control | Yes |
| Operating Temperature | 0° to 60°C (32° to 140°F) |
| Outlets | 8XC13 |
| Number of Outputs C13 | 8 |
| Number of Outputs C19 | 0 |
| Amperage Rating | 16A |
| Mounting Direction | Horizontal |
| ETIM Class | EC002762 |
| ETIMI CidSS | EC002/02 |
| Fitted With: | Ampere Meter Display Mounting material |
| | |
| Electrical Connection | Connecting cord with plug |
| Evaluation | At distance |
| Mounting Dimension (metrical) | 203 |
| Mounting Dimension (standardised) | 482.6 mm (19 inch) |
| Switchable | Yes |
| | |
| Over Voltage Category | 2 |
| | |
| Wattage | 3.84 kW max |
| • • • • • • • • • • • • • • • • • • • | OUT ATT HUX |
| Communication | HITTO HITTOC CCL. Tolock FTD CNIMO CMTD DNC DHCD LDAD DADHIC |
| | HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS |
| SNMP | Yes |
| Mass Configuration | Yes |
| | |
| Package Contents | PDU mounting accessories network cable configuration cable splitter for daisy-chaining Quickstart Safety Instructions |
| | |
| Number of Outputs C20 | 0 |
| Num of Outputs PC (SCHUKO) | 0 |
| Number of Outputs (Other) | 0 |
| Number of Outlets with Earth Pin | 8 |

| Color | Black |
|-------|-------|

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)

Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])

| (ecl@ss10.0.1-2/-14-26-90 [AKN612013]) | | |
|--|----|---------------------------|
| Mounting dimension (standardised) | | 482.6 mm (19 inch) |
| Mounting dimension | mm | |
| Mounting direction | | Horizontal |
| Electrical connection | | Connecting cord with plug |
| Type of electric connection | | C20 |
| Cable length | m | 3 |
| Number of socket outlets with protective contact | | 0 |
| Number of socket outlets with earth pin | | 8 |
| Number of C13 socket outlets | | 8 |
| Number of C19 socket outlets | | 0 |
| Number of C20 socket outlets | | 0 |
| Number of UK BS1363 sockets | | |
| number of socket outlets swiss standard type 13 | | |
| number of socket outlets swiss standard type 15 | | |
| number of socket outlets swiss standard type 23 | | |
| number of socket outlets swiss standard type 25 | | |
| Number of other socket outlets | | |
| Number of height units | | |
| Length | mm | 445 |
| Width | mm | 44 |
| Height | mm | 203 |
| Depth | mm | 445 |
| Supply voltage | V | |
| Over voltage category | | 2 |
| Mains filter | | No |
| Switchable | | Yes |
| SNMP | | Yes |
| With display | | Yes |
| Evaluation | | At distance |
| With LED indication | | No |
| With fuse | | No |
| Ampere meter | | Yes |
| With temperature measurement | | No |
| With mounting material | | Yes |
| | | |